

# K-FRONTFIX



Kunststoff Kabelverschraubungen / plastic cable glands

<b>Ausführung</b> construction	Standard standard
<b>Werkstoff</b> material	Polyamid PA6 / CR polyamide PA/ CR
<b>Temperatur</b> temperature	-20°C - +100°C
<b>kurzzeitig</b> short term	-30°C - +150°C
<b>Schutzart</b> protection	IP68
<b>Besonderheit</b> specials	Dichtung über Klemmkäfig sealing by clamping cage



FRONTFIX - UNLÖK

## schwarz / black / RAL9005

Art. Nr. art. no.	Gewinde thread	für Kabel for cable	SW1 mm	SW2 mm	GL mm	H mm	VPE Stk. unit pcs.
K-FFIXBM1610	M16	5,0 - 10,0	22	22	9,0	4,25	100
K-FFIXBM2012	M20	6,0 - 12,0	24	24	9,0	41,5	50
K-FFIXBM2013	M20	7,0 - 13,0	25	25	9,0	41,5	50
K-FFIXBM2517	M25	11,0 - 17,0	29	29	9,0	43,5	25
K-FFIXBM3221	M32	15,0 - 21,0	36	36	9,0	49,5	25
K-FFIXBM4028	M40	19,0 - 28,0	46	46	11,5	56,0	20

## hellgrau / light grey / RAL7035

Art. Nr. art. no.	Gewinde thread	für KaGel for caGel	SW1 mm	SW2 mm	GL mm	H mm	VPE Stk. unit pcs.
K-FFIXGM1610	M16	5,0 - 10,0	22	22	9,0	4,25	100
K-FFIXGM2012	M20	6,0 - 12,0	24	24	9,0	41,5	50
K-FFIXGM2013	M20	7,0 - 13,0	25	25	9,0	41,5	50
K-FFIXGM2517	M25	11,0 - 17,0	29	29	9,0	43,5	25
K-FFIXGM3221	M32	15,0 - 21,0	36	36	9,0	49,5	25
K-FFIXGM4028	M40	19,0 - 28,0	46	46	11,5	56,0	20

## grau / grey / RAL7001

Art. Nr. art. no.	Gewinde thread	für KaGel for caGel	SW1 mm	SW2 mm	GL mm	H mm	VPE Stk. unit pcs.
K-FFIXGM1610	M16	5,0 - 10,0	22	22	9,0	4,25	100
K-FFIXGM2012	M20	6,0 - 12,0	24	24	9,0	41,5	50
K-FFIXGM2013	M20	7,0 - 13,0	25	25	9,0	41,5	50
K-FFIXGM2517	M25	11,0 - 17,0	29	29	9,0	43,5	25
K-FFIXGM3221	M32	15,0 - 21,0	36	36	9,0	49,5	25
K-FFIXGM4028	M40	19,0 - 28,0	46	46	11,5	56,0	20

## FRONTFIX - UNLÖK

Art. Nr. art. no.	Größe size	D mm	D2 mm	H mm	VPE Stk. unit pcs.
UNLÖK16	M16	16	20	13	10
UNLÖK20	M20	20	24	13	10
UNLÖK25	M25	25	29	13	10
UNLÖK32	M32	32	36	13	10
UNLÖK40	M40	40	44	15,5	10

