


# X-LF



<b>Ausführung</b> construction	Standard standard
<b>Werkstoff</b> material	Edelstahl/PA6 stainless steel/PA6
<b>Dichting</b> sealing	Chloropen CR chloroprene CR
<b>Temperatur</b> temperature	-40°C - +100°C kurz / short +150°C
<b>Schutzart</b> protection	IP68
<b>Besonderheit:</b> specials:	Dichtung über Klemmkäfig sealing by clamping cage



### Gewindeart metrisch

Art. Nr. art. no.	Gewinde thread	für Kabel for cable	SW mm	L mm	H mm	VPE Stk. unit pcs.
X-LFM1205	M12	2,0 - 5,0	14	6,0	24,0	50
X-LFM1206	M12	3,0 - 6,5	14	6,0	24,0	50
X-LFM1607	M16	3,0 - 7,0	17	6,5	28,0	50
X-LFM1610	M16	4,0 - 10,0	17	6,0	28,0	50
X-LFM2010	M20	5,0 - 10,0	22	7,5	31,0	50
X-LFM2013	M20	6,0 - 13,0	22	7,5	31,0	50
X-LFM2014	M20	8,0 - 14,0	22	6,0	30,0	50
X-LFM2513	M25	7,0 - 13,0	27	7,5	34,0	25
X-LFM2517	M25	9,0 - 17,0	27	7,5	34,0	25
X-LFM2519	M25	12,0 - 19,0	30	7,0	35,0	25
X-LFM3215	M32	9,0 - 16,0	36	8,0	35,0	25
X-LFM3221	M32	11,0 - 21,0	36	8,0	35,0	25
X-LFM3222	M32	15,0 - 22,0	34	8,0	38,0	10
X-LFM4023	M40	15,0 - 23,0	46	8,0	39,0	10
X-LFM4028	M40	22,0 - 28,0	44	8,0	43,0	10
X-LFM5029	M50	20,0 - 29,0	55	10,0	48,0	5
X-LFM5035	M50	24,0 - 35,0	55	10,0	48,0	5
X-LFM5036	M50	28,0 - 36,0	54	9,0	52,0	5
X-LFM6342	M63	28,0 - 42,0	70	10,0	50,0	5
X-LFM6348	M63	32,0 - 48,0	70	10,0	50,0	5
X-LFM6349	M63	34,0 - 49,0	66	10	58,0	5

Auf Anfrage  
on request

weitere Gewindearten ( Zoll, NPT )  
more thread types ( GAS , NPT ) ✓

Viton Dichteinsätze +230°C  
Viton inserts +230°C ✓

weitere Gewindelängen  
more thread lengths ✓

Mehrfacheinsätze  
multiple clamping inserts ✓

Edelstahl V4A, 1.4571  
stainless steel 1.4571 ✓

Edelstahl V4A, 1.4404  
stainless steel 1.4404 ✓