


Ausführung construction	Standard standard
Werkstoff material	Messing vernickelt/PA6 nickel-plated brass/PA6
Dichtring sealing	Chloropren CR O-RING NBR
Temperatur temperature	-40°C - +100°C
kurzzeitig short term	+150°C
Schutzart protection	IP68 / IP69
Besonderheit specials	Dichtung über Klemmkäfig sealing by clamping cage



Gewindeart metrisch / thread metric

Art. Nr. art. no.	Gewinde thread	für Kabel for cable	SW mm	L mm	H mm	VPE Stk. unit pcs.
M-LFM1205	M12	2 - 5	14	5	25	50
M-LFM1206	M12	3 - 6,5	14	5	25	50
M-LFM1606	M16	2 - 6	17	7	33	50
M-LFM1608	M16	3 - 8	17	5,5	28	50
M-LFM1610	M16	4,5 - 10	17	6	28	50
M-LFM2009	M20	5 - 9	22	6	30	50
M-LFM2012	M20	6 - 12	22	6	30	50
M-LFM2013	M20	8 - 13	22	6	30	50
M-LFM2512	M25	7 - 12	24	8	42	25
M-LFM2514	M25	8 - 14	30	7	35	25
M-LFM2517	M25	11 - 18	30	7	35	25
M-LFM3216	M32	9 - 16	30	9	48	10
M-LFM3218	M32	13 - 19	34	8	35	10
M-LFM3221	M32	15 - 21	34	8	38	10
M-LFM4020	M40	12 - 20	44	8	43	10
M-LFM4023	M40	16 - 23	44	8	43	10
M-LFM4025	M40	18 - 25	40	9	53	10
M-LFM4028	M40	19 - 28	44	8	52	10
M-LFM5026	M50	20 - 26	54	9	52	5
M-LFM5029	M50	21 - 29	54	9	52	5
M-LFM5032	M50	22 - 32	50	9	57	5
M-LFM5035	M50	25 - 35	54	9	52	5
M-LFM5038	M50	27 - 38	58	9	61	5
M-LFM6338	M63	27 - 38	66	10	54	5
M-LFM6342	M63	32 - 42	64	14	65	5
M-LFM6344	M63	34 - 44	64	14	65	5
M-LFM6348	M63	39 - 48	66	10	54	5

Gewindeart PG / thread PG

Art. Nr. art. no.	Gewinde thread	für Kabel for cable	SW mm	L mm	H mm	VPE Stk. unit pcs.
M-LFP0705	PG07	2 - 5	14	6	28	50
M-LFP0706	PG07	3 - 6,5	14	6	28	50
M-LFP0906	PG09	2 - 6	17	6	28	50
M-LFP0908	PG09	4 - 8	17	6	28	50
M-LFP1107	PG11	3 - 7	20	6	31	50
M-LFP1110	PG11	5 - 10	20	6	31	50
M-LFP1309	PG13,5	5 - 9	22	6,5	31	50
M-LFP1312	PG13,5	6 - 12	22	6,5	31	50
M-LFP1612	PG16	7 - 12	24	6,5	34	25
M-LFP1614	PG16	10 - 14	24	6,5	34	25
M-LFP2116	PG21	9 - 16	30	7	39	25
M-LFP2118	PG21	13 - 18	30	7	39	25
M-LFP2920	PG29	12 - 20	40	8	47	20
M-LFP2925	PG29	18 - 25	40	8	47	20
M-LFP3626	PG36	20 - 26	50	10	57	15
M-LFP3632	PG36	22 - 32	50	10	57	15
M-LFP4231	PG42	25 - 31	58	12	60	12
M-LFP4238	PG42	30 - 38	58	12	60	12
M-LFP4835	PG48	29 - 35	64	14	63	12
M-LFP4844	PG48	34 - 44	64	14	63	12

Auf Anfrage
on request



Multi-einsätze
multi-inserts



Langes Gewinde
long thread



Flachkabeleinsätze
flat cable inserts