



M-LFKV-EMV



Ausführung construction	Standard EMV standard EMC
Werkstoff material	Messing vernickelt nickel-plated brass
Dichtring sealing	Chloropren CR chloroprene CR
Temperatur temperature	-40°C - +100°C kurz / short +150°C
Schutzart protection	IP68

Besonderheit:
specials:

Verschraubung mit Klemmkäfig und EMV-Kralen.
Cable gland with clamping cage and EMC-claws.



Standard

Art. Nr. art. no.	Gewinde thread	für Kabel for cable	SW mm	L mm	H mm	VPE Stk. unit pcs.
M-LFKVM1206EMV	M12	2,0 - 6,5	14	6	22,0	50
M-LFKVM1610EMV	M16	5,0 - 10,0	20	7	29,0	50
M-LFKVM2012EMV	M20	6,0 - 12,0	22	8	27,5	50
M-LFKVM2517EMV	M25	11,0 - 17,0	27	8	30,7	25
M-LFKVM3221EMV	M32	15,0 - 21,0	34	8	38,0	10
M-LFKVM4028EMV	M40	19,0 - 28,0	43	9	43,0	5
M-LFKVM5038EMV	M50	27,0 - 38,0	58	9	54,5	5
M-LFKVM6344EMV	M63	34,0 - 44,0	64	14	57,0	5

langes Gewinde / long thread

Art. Nr. art. no.	Gewinde thread	für Kabel for cable	SW mm	GL mm	H mm	VPE Stk. unit pcs.
M-LFKVM1206EMVL	M12	2,0 - 6,5	14	12	22,0	50
M-LFKVM1610EMVL	M16	5,0 - 10,0	20	12	29,0	50
M-LFKVM2012EMVL	M20	6,0 - 12,0	22	12	27,5	50
M-LFKVM2517EMVL	M25	11,0 - 17,0	27	15	30,7	25
M-LFKVM3221EMVL	M32	15,0 - 21,0	34	15	38,0	10
M-LFKVM4028EMVL	M40	19,0 - 28,0	43	15	43,0	5
M-LFKVM5038EMVL	M50	27,0 - 38,0	58	15	54,5	5
M-LFKVM6344EMVL	M63	34,0 - 44,0	64	18	57,0	5

Auf Anfrage
on request

Viton Dichteinsätze +230°C
viton Inserts +230°C



weitere Materialien (VA)
more materials (INOX)



weitere Gewindearten (Zoll, NPT)
more thread types (GAS , NPT)

