


M-LFV



Ausführung construction	Hochtemperatur high temperature
Werkstoff material	Messing vernickelt nickel-plated brass
Dichtring sealing	VITON
Temperatur temperature	-25°C - +230°C
Schutzart protection	IP68

Besonderheit:
specials:

Dichtung über
Klemmkäfig
sealing by
clamping cage



Gewindeart metrisch

Art. Nr. art. no.	Gewinde thread	für Kabel for cable	SW mm	L mm	H mm	VPE Stk. unit pcs.
M-LFVM1207	M12	5,0 - 7,0	14	5	14	50
M-LFVM1607	M16	5,0 - 7,0	17	5,5	17	50
M-LFVM1610	M16	8,0 - 10,0	17	5,5	17	50
M-LFVM2010	M20	7,0 - 10,0	22	6	22	50
M-LFVM2014	M20	11,0 - 14,0	22	6	22	50
M-LFVM2514	M25	11,0 - 14,0	30	7	30	25
M-LFVM2519	M25	15,0 - 19,0	30	7	30	25
M-LFVM3218	M32	15,0 - 18,0	34	8	34	25
M-LFVM3222	M32	19,0 - 22,0	34	8	34	25
M-LFVM4024	M40	21,0 - 24,0	44	8	44	10
M-LFVM4028	M40	25,0 - 28,0	44	8	44	10

Gewindeart PG

Art. Nr. art. no.	Gewinde thread	für Kabel for cable	SW mm	GL mm	H mm	VPE Stk. unit pcs.
M-LFVP0707	PG07	5,0 - 7,0	14	5	14	100
M-LFVP0907	PG09	5,0 - 7,0	17	5,5	17	50
M-LFVP0910	PG09	8,0 - 10,0	17	5,5	17	50
M-LFVP1107	PG11	5,0 - 7,0	20	6	20	50
M-LFVP1110	PG11	8,0 - 10,0	20	6	20	50
M-LFVP1310	PG13,5	7,0 - 10,0	22	7	22	25
M-LFVP1314	PG13,5	11,0 - 14,0	22	7	22	25
M-LFVP2114	PG21	11,0 - 14,0	30	8	30	25
M-LFVP2119	PG21	15,0 - 19,0	30	8	30	25
M-LFVP2924	PG29	21,0 - 24,0	40	8	40	25
M-LFVP2928	PG29	25,0 - 28,0	40	8	40	25

Auf Anfrage
on request

weitere Materialien (VA)
more materials (INOX)



weitere Gewindearten (Zoll, NPT)
more thread types (GAS, NPT)

