




Ausführung construction	Standard (PA) standard (PA)
	Hochtemperatur (PVDF) high temperature (PVDF)
Werkstoff material	Edelstahl stainless steel
Dichtring sealing	PA / PVDF O-RING NBR / FKMM
Temperatur temperature	-40°C - +100°C (PA) -35°C - +150°C (HT)
Schutzart protection	IP68 - 10 bar / IP69K
Besonderheit specials	Verschraubung mit Klemmkäfig Cable gland with clamping cage

Standard PA / standard PA

Art. Nr. V2A art. no. 1.4305	Art. Nr. V4A art. no. 1.4404	Gewinde thread	für Kabel for cable	SW mm	L mm	H mm	VPE Stk. unit pcs.
X-LHSKM1206PA	X-LHSKM1206PAV4A	M12 x 1,5	3 - 6,5	14	6,5	19	50
X-LHSKM1205PA	X-LHSKM1205PAV4A	M12 x 1,5	2 - 5	14	6,5	19	50
X-LHSKM1610PA	X-LHSKM1610PAV4A	M16 x 1,5	5 - 10	22	6	22	50
X-LHSKM1607PA	X-LHSKM1607PAV4A	M16 x 1,5	3 - 7	22	6	22	50
X-LHSKM2014PA	X-LHSKM2014PAV4A	M20 x 1,5	10 - 14	24	6	23	50
X-LHSKM2012PA	X-LHSKM2012PAV4A	M20 x 1,5	7 - 12	24	6	23	50
X-LHSKM2518PA	X-LHSKM2518PAV4A	M25 x 1,5	13 - 18	30	7	24	50
X-LHSKM2516PA	X-LHSKM2516PAV4A	M25 x 1,5	9 - 16	30	7	24	50
X-LHSKM3225PA	X-LHSKM3225PAV4A	M32 x 1,5	18 - 25	41	8	31	25
X-LHSKM3220PA	X-LHSKM3220PAV4A	M32 x 1,5	13 - 20	41	8	31	25
X-LHSKM4032PA	X-LHSKM4032PAV4A	M40 x 1,5	22 - 32	50	8	37	10
X-LHSKM4026PA	X-LHSKM4026PAV4A	M40 x 1,5	20 - 26	50	8	37	10
X-LHSKM5038PA	X-LHSKM5038PAV4A	M50 x 1,5	32 - 38	60	9	37	5
X-LHSKM5031PA	X-LHSKM5031PAV4A	M50 x 1,5	25 - 31	60	9	37	5
X-LHSKM6344PA	X-LHSKM6344PAV4A	M63 x 1,5	37 - 44	64 / 68	10	38	5
X-LHSKM6335PA	X-LHSKM6335PAV4A	M63 x 1,5	29 - 35	64 / 68	10	38	5

Hochtemperatur PVDF / high temperature PVDF

Art. Nr. V2A art. no. 1.4305	Art. Nr. V4A art. no. 1.4404	Gewinde thread	für Kabel for cable	SW mm	L mm	H mm	VPE Stk. unit pcs.
X-LHSKM1206	X-LHSKM1206V4A	M12 x 1,5	3 - 6,5	14	6,5	19	50
X-LHSKM1205	X-LHSKM1205V4A	M12 x 1,5	2 - 5	14	6,5	19	50
X-LHSKM1610	X-LHSKM1610V4A	M16 x 1,5	5 - 10	22	6	22	50
X-LHSKM1607	X-LHSKM1607V4A	M16 x 1,5	3 - 7	22	6	22	50
X-LHSKM2014	X-LHSKM2014V4A	M20 x 1,5	10 - 14	24	6	23	50
X-LHSKM2012	X-LHSKM2012V4A	M20 x 1,5	7 - 12	24	6	23	50
X-LHSKM2518	X-LHSKM2518V4A	M25 x 1,5	13 - 18	30	7	24	50
X-LHSKM2516	X-LHSKM2516V4A	M25 x 1,5	9 - 16	30	7	24	50
X-LHSKM3225	X-LHSKM3225V4A	M32 x 1,5	18 - 25	41	8	31	25
X-LHSKM3220	X-LHSKM3220V4A	M32 x 1,5	13 - 20	41	8	31	25
X-LHSKM4032	X-LHSKM4032V4A	M40 x 1,5	22 - 32	50	8	37	10
X-LHSKM4026	X-LHSKM4026V4A	M40 x 1,5	20 - 26	50	8	37	10
X-LHSKM5038	X-LHSKM5038V4A	M50 x 1,5	32 - 38	60	9	37	5
X-LHSKM5031	X-LHSKM5031V4A	M50 x 1,5	25 - 31	60	9	37	5
X-LHSKM6344	X-LHSKM6344V4A	M63 x 1,5	37 - 44	64 / 68	10	38	5
X-LHSKM6335	X-LHSKM6335V4A	M63 x 1,5	29 - 35	64 / 68	10	38	5



Auf Anfrage
on request



Multieinsätze
multi-inserts



Langes Gewinde
long thread



Flachkableinsätze
flat cable inserts