


X-UNI-DICHT



Ausführung construction	Standard standard
Werkstoff material	Edelstahl stainless steel
Dichtring sealing	TPE
Temperatur temperature	-40°C - +130°C
Schutzart protection	IP68
Besonderheit: specials:	VA-Verschraubung mit Vollgummi Dichteinsatz. Stainless cable gland with solid rubber clamping insert.



Gewindeart metrisch

Art. Nr. art. no.	Gewinde thread	für Kabel for cable	SW mm	GL mm	VPE Stk. unit pcs.
X-UNIM1004	M10	1,0 - 4,5	14	5,0	1
X-UNIM1006	M10	4,0 - 6,5	14	5,0	1
X-UNIM1204	M12	1,0 - 4,5	14	6,0	1
X-UNIM1206	M12	4,0 - 6,5	14	6,0	1
X-UNIM1606	M16	4,0 - 6,5	17	6,5	1
X-UNIM1608	M16	5,0 - 8,0	17	6,5	1
X-UNIM1609	M16	6,5 - 9,5	17	6,5	1
X-UNIM2006	M20	4,0 - 6,5	22	7,0	1
X-UNIM2008	M20	5,0 - 8,0	22	7,0	1
X-UNIM2009	M20	6,5 - 9,5	22	7,0	1
X-UNIM2010	M20	7,0 - 10,5	22	7,0	1
X-UNIM2013	M20	9,0 - 13,0	22	7,0	1
X-UNIM2506	M25	4,0 - 6,5	27	7,5	1
X-UNIM2508	M25	5,0 - 8,0	27	7,5	1
X-UNIM2509	M25	6,5 - 9,5	27	7,5	1
X-UNIM2510	M25	7,0 - 10,5	27	7,5	1
X-UNIM2513	M25	9,0 - 13,0	27	7,5	1
X-UNIM2515	M25	11,5 - 15,5	27	7,5	1

Art. Nr. art. no.	Gewinde thread	für Kabel for cable	SW mm	GL mm	VPE Stk. unit pcs.
X-UNIM3210	M32	7,0 - 10,5	36	8,0	1
X-UNIM3213	M32	9,0 - 13,0	36	8,0	1
X-UNIM3215	M32	11,5 - 15,5	36	8,0	1
X-UNIM3218	M32	14,0 - 18,0	36	8,0	1
X-UNIM3221	M32	17,0 - 21,0	36	8,0	1
X-UNIM4015	M40	11,5 - 15,5	46	8,0	1
X-UNIM4018	M40	14,0 - 18,0	46	8,0	1
X-UNIM4021	M40	17,0 - 21,0	46	8,0	1
X-UNIM4025	M40	20,0 - 25,0	46	8,0	1
X-UNIM4028	M40	24,0 - 28,0	46	8,0	1
X-UNIM4032	M40	27,0 - 32,0	50	8,0	1
X-UNIM5032	M50	27,0 - 32,0	55	10,0	1
X-UNIM5034	M50	29,0 - 34,0	55	10,0	1
X-UNIM5036	M50	32,0 - 36,0	55	10,0	1
X-UNIM5041	M50	36,0 - 41,0	60	10,0	1
X-UNIM6345	M63	39,5 - 45,0	70	10,0	1
X-UNIM6352	M63	47,0 - 52,0	70	10,0	1

Auf Anfrage
on request

Mehrfacheinsätze
multiple clamping inserts ✓

Silikon Einsatz
silicone insert ✓

ungebohrte Dichteinsätze
undrilled inserts ✓

weitere Gewindelängen
more thread lengths ✓

TPE-V Einsatz
TPE-V insert ✓

EMV Ausführung
EMC type ✓