


X-Blueglobe



Ausführung construction	große Klemmbereiche large clamping range
Werkstoff material	Edelstahl stainless steel
Dichtring sealing	TPE
Temperatur temperature	-40°C - +130°C
Schutzart protection	IP69K
Besonderheit: specials:	Verschraubung mit Vollgummi-Dicht- einsatz. Cable gland with solid rubber clamping insert.



Standard

Art. Nr. art. no.	Gewinde thread	für Kabel for cable	SW mm	GL mm	H mm	VPE Stk. unit pcs.
X-BGM1208	M12	2,0 - 8,0	17	5,0	21,0	50
X-BGM1611	M16	4,0 - 11,0	20	6,0	25,0	50
X-BG2014	M20	5,0 - 14,0	24	6,5	29,0	50
X-BGM2520	M25	11,0 - 20,0	30	7,5	30,0	50
X-BGM3225	M32	15,0 - 25,0	36	8,0	32,0	25
X-BGM4032	M40	20,0 - 32,0	45	8,0	35,0	10
X-BGM5042	M50	31,0 - 42,0	57	10,0	39,0	5
X-BGM6354	M63	41,0 - 54,0	68	10,0	40,0	5
X-BGM7565	M75	54,0 - 65,0	81	15,0	47,0	5
X-BGM8577	M85	65,0 - 77,0	95	15,0	49,0	1

langes Gewinde / long thread

Art. Nr. art. no.	Gewinde thread	für Kabel for cable	SW mm	GL mm	H mm	VPE Stk. unit pcs.
X-BGM1208L	M12	2,0 - 8,0	17	15,0	21,0	50
X-BG1M611L	M16	4,0 - 11,0	20	15,0	25,0	50
X-BGM2014L	M20	5,0 - 14,0	24	15,0	29,0	50
X-BGM2520L	M25	11,0 - 20,0	30	15,0	30,0	50
X-BGM3225L	M32	15,0 - 25,0	36	15,0	32,0	25
X-BGM2032L	M40	20,0 - 32,0	45	15,0	35,0	10
X-BGM5042L	M50	31,0 - 42,0	57	15,0	39,0	5
X-BGM6354L	M63	41,0 - 54,0	68	15,0	40,0	5

Auf Anfrage
on request

Silikon Einsatz
silicone insert ✓

EMV Ausführung
EMC option ✓