

Metall Kabelverschraubungen / metal cable glands


Ausführung construction	Standard standard
	Hochtemperatur (HT) high temperature (HT)
Werkstoff material	Messing vernickelt, Edelstahl nickel-plated brass, stainless steel
Dichtring sealing	TPE / Silikon TPE / silicone
Temperatur temperature	-40°C - +130°C -60°C - +200°C (HT)
Schutzart protection	IP 68 - 15 bar / IP69 / Type 4X
Besonderheit specials	Verschraubung mit Vollgummi-Dichteinsatz Cable gland with solid rubber clamping insert



Art. Nr. art. no.	Art. Nr. HT art. no. HT	Gewinde thread	für Kabel for cable	SW mm	L mm	H mm	VPE Stk. unit pcs.
M-BGM806	M-BGM806HT	M8	3 - 6	11	5	22	50
M-BGM1006	M-BGM1006HT	M10	1,5 - 6	13	6	20	50
M-BGM1208	M-BGM1208HT	M12	2 - 8	17	5	21	50
M-BGM1611	M-BGM1611HT	M16	4 - 11	20	6	25	50
M-BGM2014	M-BGM2014HT	M20	5 - 14	24	6,5	29	50
M-BGM2520	M-BGM2520HT	M25	11 - 20	30	7,5	30	50
M-BGM3225	M-BGM3225HT	M32	15 - 25	36	8	32	25
M-BGM4032	M-BGM4032HT	M40	20 - 32	45	8	35	10
M-BGM5042	M-BGM5042HT	M50	31 - 42	57	10	39	5
M-BGM6354	M-BGM6354HT	M63	41 - 54	68	10	40	5
M-BGM7565	M-BGM7565HT	M75	54 - 65	81	15	47	5
M-BGM8577	M-BGM8577HT	M85	65 - 77	95	15	49	1

Art. Nr. V2A art. no. 1.4303	Art. Nr. V2A HT art. no. 1.4303 HT	Gewinde thread	für Kabel for cable	SW mm	L mm	H mm	VPE Stk. unit pcs.
X-BGM1208	X-BGM1208HT	M12	2 - 8	17	5	21	50
X-BGM1611	X-BGM1611HT	M16	4 - 11	20	6	25	50
X-BGM2014	X-BGM2014HT	M20	5 - 14	24	6,5	29	50
X-BGM2520	X-BGM2520HT	M25	11 - 20	30	7,5	30	50
X-BGM3225	X-BGM3225HT	M32	15 - 25	36	8	32	25
X-BGM4032	X-BGM4032HT	M40	20 - 32	45	8	35	10
X-BGM5042	X-BGM5042HT	M50	31 - 42	57	10	39	5
X-BGM6354	X-BGM6354HT	M63	41 - 54	68	10	40	5
X-BGM7565	X-BGM7565HT	M75	54 - 65	81	15	47	5
X-BGM8577	X-BGM8577HT	M85	65 - 77	95	15	49	1

Art. Nr. V4A art. no. 1.4571	Art. Nr. V4A HT art. no. 1.4571 HT	Gewinde thread	für Kabel for cable	SW mm	L mm	H mm	VPE Stk. unit pcs.
X-BGM1208V4A	X-BGM1208HTV4A	M12	2 - 8	17	5	21	50
X-BGM1611V4A	X-BGM1611HTV4A	M16	4 - 11	20	6	25	50
X-BGM2014V4A	X-BGM2014HTV4A	M20	5 - 14	24	6,5	29	50
X-BGM2520V4A	X-BGM2520HTV4A	M25	11 - 20	30	7,5	30	50
X-BGM3225V4A	X-BGM3225HTV4A	M32	15 - 25	36	8	32	25
X-BGM4032V4A	X-BGM4032HTV4A	M40	20 - 32	45	8	35	10
X-BGM5042V4A	X-BGM5042HTV4A	M50	31 - 42	57	10	39	5
X-BGM6354V4A	X-BGM6354HTV4A	M63	41 - 54	68	10	40	5
X-BGM7565V4A	X-BGM7565HTV4A	M75	54 - 65	81	15	47	5
X-BGM8577V4A	X-BGM8577HTV4A	M85	65 - 77	95	15	49	1



EMV Ausführung auf Anfrage.
EMC option on request.

