

DG-NEO / DG-TPE



Ausführung construction	Durchführungsstülpe grommet
Werkstoff material	Neopren (DG-NEO) TPE (DG-TPE)
Temperatur temperature	-30°C - +90°C (NEO) -50°C - +125°C (TPE)
Schutzart protection	-
Gemäß according to	-



TYP / TYPE DG-NEO

Art. Nr. schwarz art. no. black	Art. Nr. grau art. no. grey	Loch Ø M hole Ø M	Ø A mm	Ø B mm	Ø C mm	E mm	F1 mm	F2 mm	M mm	VE/St. PU/pcs.
DG28051	-	M16	9,0	16,0	20,0	2,0	2,5	2,5	1,0	100
DG28052	DG280520	M20	13,5	20,0	25,0	2,0	2,5	2,5	1,0	100
DG28053	DG280530	M25	18,5	25,0	30,5	2,0	2,5	2,5	1,0	100
DG28054	DG280540	M32	25,0	32,0	39,0	2,0	3,0	3,0	1,0	100
DG28055	-	M40	31,0	40,0	47,0	2,5	3,8	3,8	1,0	50
DG28056	-	M50	39,0	50,0	57,0	2,5	3,8	3,8	1,0	50
DG28057	-	M63	53,0	63,0	75,0	2,5	3,8	3,8	1,0	50
DG28059	-	M68	53,0	68,0	75,0	2,5	3,8	3,8	1,5	50
DG28058	-	M75	65,0	75,0	87,0	2,5	3,8	3,8	1,0	50

Art. Nr. schwarz art. no. black	Art. Nr. grau art. no. grey	Loch Ø PG hole Ø PG	Ø A mm	Ø B mm	Ø C mm	E mm	F1 mm	F2 mm	M mm	VE/St. PU/pcs.
DG28020	-	PG 9	9,0	15,5	20,0	1,0	3,5	2,5	1,0	100
DG28021	DG280210	PG 9	9,0	15,5	20,0	2,0	2,5	2,5	1,0	100
DG28022	DG280220	PG 11	11,0	18,5	23,0	2,0	2,5	2,5	1,0	100
DG28023	DG280230	PG 13,5	13,5	20,5	25,0	2,0	2,5	2,5	1,0	100
DG28024	DG280240	PG 16	16,0	22,5	27,5	2,0	2,5	2,5	1,0	100
DG28025	DG280250	PG 21	21,0	28,0	35,0	2,0	3,0	3,0	1,0	100
DG28026	-	PG 29	29,0	37,0	44,0	2,0	3,5	3,5	1,0	50
DG28027	-	PG 36	36,0	47,0	54,0	2,5	3,8	3,8	1,0	50
DG28028	-	PG 48	48,0	60,0	68,0	2,5	3,8	3,8	1,0	50
DG28029	-	-	53,0	64,0	75,0	2,5	3,8	3,8	1,5	50
DG28030	-	-	69,0	79,0	90,0	2,5	3,8	3,8	1,5	50

TYP / TYPE DG-TPE

Art. Nr. schwarz art. no. black	Art. Nr. grau art. no. grey	Loch Ø M hole Ø M	Ø A mm	Ø B mm	Ø C1 mm	Ø C2 mm	E mm	F1 mm	F2 mm	M mm	VE/St. PU/pcs.
DG28137	DG281370	M20	13,5	20,0	24,0	24,0	2,0	2,5	2,5	1,0	100
DG28138	DG281380	M25	21,0	25,0	34,5	31,5	2,0	3,0	3,0	1,0	100
DG28139	DG281390	M32	29,0	32,0	43,5	39,0	2,2	3,7	3,7	1,3	100

Art. Nr. schwarz art. no. black	Art. Nr. grau art. no. grey	Loch Ø PG hole Ø PG	Ø A mm	Ø B mm	Ø C1 mm	Ø C2 mm	E mm	F1 mm	F2 mm	M mm	VE/St. PU/pcs.
DG28135	DG281350	PG 9	9,0	15,0	20,0	18,0	2,0	2,5	2,5	1,0	100
DG28136	DG281360	PG 11	11,0	18,0	22,5	21,5	2,0	2,5	2,5	1,0	100
DG28007	DG280070	PG 13,5	13,5	20,0	24,0	24,0	2,0	2,5	2,5	1,0	100
DG28008	DG280080	PG 16	16,0	22,0	27,5	26,0	2,0	2,7	2,7	1,0	100
DG28009	DG280090	PG 21	21,0	28,0	34,5	34,5	2,0	3,0	3,0	1,0	100
DG28010	-	PG 29	29,0	37,0	43,5	43,5	2,2	3,7	3,7	1,3	50
DG28037	-	PG 36	35,5	47,0	52,5	52,5	2,5	3,8	3,8	1,3	50
DG28038	-	PG 48	47,0	59,0	67,0	67,0	2,5	4,0	4,0	1,5	50