

M-VSC / M-TPE



Ausführung construction	Verschlusschraube plug
Werkstoff material	Messing vernickelt nickel-plated brass
Temperatur temperature	bis / up to +200°C
Schutzart protection	-
Gemäß according to	-



M-TPE



M-VSC

Serie/series M-TPE

Art. Nr. art. no.	AG male	GL mm	L mm	SW mm	VPE Stk. unit pcs.
M-TPE16	M16	8	13	19	20
M-TPE20	M20	8	13	22	20
M-TPE25	M25	9	14	30	10
M-TPE32	M32	9	14	35	10
M-TPE40	M40	9	17	42	5
M-TPE50	M50	13	23	55	5
M-TPE63	M63	16	24	81	2

Art. Nr. art. no.	AG male	GL mm	L mm	SW mm	VPE Stk. unit pcs.
M-TPE01	PG07	8	12	14	20
M-TPE02	PG09	8	12	17	20
M-TPE03	PG11	8	13	20	20
M-TPE04	PG13,5	9	14	22	20
M-TPE05	PG16	9	14	24	20
M-TPE06	PG21	10	15	30	10
M-TPE07	PG29	10	15	38	10
M-TPE08*	PG36	13	20	50	5
M-TPE09*	PG42	12	21	55	5
M-TPE10*	PG48	15	25	60	2

Art. Nr. art. no.	AG male	GL mm	L mm	SW mm	VPE Stk. unit pcs.
M-TPE1	1/4"	8	12,0	15	20
M-TPE2	3/8"	8	13,0	19	20
M-TPE3	1/2"	9	14,0	24	20
M-TPE4	3/4"	9	14,0	30	10
M-TPE5	1"	10	15,5	38	10
M-TPE6*	1 1/4"	15	22,0	42	5
M-TPE7*	1 1/2"	15	22,0	50	5
M-TPE8*	2"	17	25,0	60	2
M-TPE9*	2 1/2"	19	29,0	75	2

Serie/series M-VSC

Art. Nr. art. no.	AG male	GL / AG mm	L mm	AD mm	VPE Stk. unit pcs.
M-VSCM12	M12	5,0	7,5	14,0	100
M-VSCM16	M16	5,0	8,0	18,0	100
M-VSCM20	M20	6,0	9,5	22,0	100
M-VSCM25	M25	7,0	11,0	28,0	100
M-VSCM32	M32	8,0	12,0	35,0	50
M-VSCM40	M40	8,0	13,0	43,0	50
M-VSCM50	M50	9,0	15,0	53,0	25
M-VSCM63	M63	10,0	16,0	66,0	10

Art. Nr. art. no.	AG male	GL / AG mm	L mm	AD mm	VPE Stk. unit pcs.
M-VSCPG07	PG07	5,0	8,0	14,0	100
M-VSCPG09	PG09	6,0	9,0	17,0	100
M-VSCPG11	PG11	6,0	9,0	20,0	100
M-VSCPG13	PG13,5	6,5	9,5	22,0	100
M-VSCPG16	PG16	6,5	9,5	24,0	100
M-VSCPG21	PG21	7,0	11,0	30,0	50
M-VSCPG29	PG29	8,0	12,0	39,0	25
M-VSCPG36	PG36	9,0	15,0	50,0	10
M-VSCPG42	PG42	10,0	16,0	57,0	10
M-VSCPG48	PG48	10,0	16,0	64,0	10