

<b>Ausführung</b> construction	Gegenmutter locknut
<b>Werkstoff</b> material	Messing vernickelt nickel-plated brass
<b>Temperatur</b> temperature	bis +200°C up to +200°C

**metrisch / metric**

Art. Nr. art. no.	Gewinde thread	SW mm	H mm	VPE Stk. unit pcs.
M-GMM06	M6	9	2,8	50
M-GMM08	M8	11	2,8	50
M-GMM10	M10	13	2,8	50
M-GMM12	M12	15	2,8	100
M-GMM16	M16	19	2,8	100
M-GMM20	M20	24	3,0	100
M-GMM25	M25	30	3,5	100
M-GMM32	M32	36	4,0	100
M-GMM40	M40	46	5,0	50
M-GMM50	M50	60	5,0	25
M-GMM63	M63	70	6,0	25


**PG**

Art. Nr. art. no.	Gewinde thread	SW mm	H mm	VPE Stk. unit pcs.
M-GMP07	PG07	15	2,8	100
M-GMP09	PG09	18	2,8	100
M-GMP11	PG11	21	3,0	100
M-GMP13	PG13,5	23	3,0	100
M-GMP16	PG16	26	3,0	100
M-GMP21	PG21	32	3,5	100
M-GMP29	PG29	41	4,0	50
M-GMP36	PG36	51	5,0	50
M-GMP42	PG42	60	5,0	25
M-GMP48	PG48	64	5,0	25

**Zoll / gas**

Art. Nr. art. no.	Gewinde thread	SW mm	H mm	VPE Stk. unit pcs.
M-GMZ014	1/4"	15	2,8	100
M-GMZ038	3/8"	20	3,0	100
M-GMZ012	1/2"	24	3,0	100
M-GMZ034	3/4"	30	3,5	100
M-GMZ100	1"	38	4,5	100
M-GMZ114	1 1/4"	46	5,0	50
M-GMZ112	1 1/2"	51	5,0	50
M-GMZ134	1 3/4"	51	5,0	50
M-GMZ200	2"	64	5,5	50
M-GMZ212	2 1/2"	80	7,0	25
M-GMZ300	3"	100	8,0	10
M-GMZ400	4"	125	1,0	1
M-GMZ500	5"	150	2,0	1

- L Länge gesamt / overall length  
 GL Gewindelänge / thread length  
 AG Außengewinde / male thread  
 IG Innengewinde / female thread  
 SW Schlüsselweite / key-width  
 H Höhe / height  
 ID Innendurchmesser / inside diameter