


<b>Ausführung</b> construction	Gegenmutter mit Schneidkante locknut with knife edge
<b>Werkstoff</b> material	Messing vernickelt nickel-plated brass
<b>Temperatur</b> temperature	bis +200°C up to +200°C


**metrisch / metric**

Art. Nr. art. no.	Gewinde thread	SW mm	H mm	VPE Stk. unit pcs.
M-GMM12EMV	M12	15	2,8	50
M-GMM16EMV	M16	19	2,8	50
M-GMM20EMV	M20	24	3,0	50
M-GMM25EMV	M25	30	3,5	50
M-GMM32EMV	M32	36	4,5	25
M-GMM40EMV	M40	46	5,0	25
M-GMM50EMV	M50	60	5,0	10
M-GMM63EMV	M63	70	6,0	10

**PG**

Art. Nr. art. no.	Gewinde thread	SW mm	H mm	VPE Stk. unit pcs.
M-GMP07EMV	PG07	15	4,7	100
M-GMP09EMV	PG09	18	4,7	100
M-GMP11EMV	PG11	21	4,7	100
M-GMP13EMV	PG13,5	23	4,7	100
M-GMP16EMV	PG16	26	4,7	100
M-GMP21EMV	PG21	32	5,2	50
M-GMP29EMV	PG29	41	5,7	50
M-GMP36EMV	PG36	51	6,5	50
M-GMP42EMV	PG42	60	6,5	25
M-GMP48EMV	PG48	64	6,5	25

- L Länge gesamt / overall length  
 GL Gewindelänge / thread length  
 AG Außengewinde / male thread  
 IG Innengewinde / female thread  
 SW Schlüsselweite / key-width  
 H Höhe / height  
 ID Innendurchmesser / inside diameter