

LIG



Ausführung construction	Gehäuse box
Werkstoff material	Edelstahl stainless steel
Dichtung sealing	PU
Temperatur temperature	-40°C - +90°C°
Schutzart protection	IP66 / 68 / 69K
Gemäß according to	-



- ! LIG - mit Befestigungsbohrung
LIG - with fixing wholes
- ! LIGO - ohne Befestigungsbohrungen
LIGO - without fixing wholes

Art. Nr. LIG art. no. LIG	Art. Nr. LIGO art. no. LIGO	Länge mm length mm	Breite mm width mm	Höhe mm height mm	VPE Stk. unit pcs.
LIG100	LIGO100	100	100	61	1
LIG101	LIGO101	150	100	61	1
LIG150	LIGO150	150	150	81	1
LIG102		200	100	61	1
LIG200	LIGO200	200	200	81	1
LIG201	LIGO201	200	200	121	1
LIG151		300	150	81	1
LIG202		300	200	81	1
LIG203	LIGO203	300	200	121	1
LIG300		300	300	121	1
LIG301		300	300	161	1
LIG380		380	380	161	1
LIG152		400	150	81	1
LIG204		400	200	121	1
LIG302		400	300	161	1
LIG303		500	300	161	1
LIG400		500	400	161	1
LIG600		600	200	121	1

Weitere verfügbare Edelstahl-Gehäuse:
Typ LIGS: Industriegehäuse mit Scharnier
(verfügbare Maße: 200x250x97 mm bis
600x380x217 mm)

Typ LKSS: Edelstahl-Kleinschaltschrank
mit scharnierter Tür (verfügbare Maße:
200x300x155 mm bis 600x760x210 mm)

Weitere Größen und
EMV-Ausführung auf Anfrage.
Weitere Dichtungen verfügbar:
Polyurethan (PU)

Other available Stainless steel boxes:
Type LIGS: Industrial housing with hinge
(available sizes: 200x250x97 mm
to 600x380x217 mm)

Type LKSS: Stainless steel compact
cabinet with hinged door (available sizes:
200x300x155 mm to 600x760x210 mm)

Additional sizes and
emc-versions on request.
Other sealings also available:
polyurethan (PU)