

M-ERW / M-ERWS




Ausführung construction	Erweiterung enlarger
Werkstoff material	Messing vernickelt nickel-plated brass
Temperatur temperature	bis +200°C up to +200°C



M-ERWS



M-ERW



M-ERW metrisch / metric

Art. Nr. art. no.	AG male	IG female	L mm	GL / AG mm	AD mm	VPE Stk unit pcs.
M-ERWM1216	M12	M16	15,0	5,0	18	100
M-ERWM1620	M16	M20	17,5	6,0	22	100
M-ERWM1625	M16	M25	20,0	6,5	27	50
M-ERWM2025	M20	M25	19,0	6,5	27	50
M-ERWM2032	M20	M32	22,0	7,0	34	50
M-ERWM2532	M25	M32	21,0	6,5	34	50
M-ERWM2540	M25	M40	24,0	7,5	43	50
M-ERWM3240	M32	M40	23,0	7,0	42	50
M-ERWM3250	M32	M50	28,0	8,0	53	25
M-ERWM4050	M40	M50	31,0	9,0	53	10
M-ERWM5063	M50	M63	31,0	9,0	66	10

M-ERWS metrisch / metric

Art. Nr. art. no.	AG male	IG female	L mm	GL / AG mm	SW mm	VPE Stk unit pcs.
M-ERWSM1216	M12	M16	17,0	6,0	17	50
M-ERWSM1620	M16	M20	17,5	6,5	22	50
M-ERWSM1625	M16	M25	20,0	6,5	27	50
M-ERWSM2025	M20	M25	20,0	7,0	27	50
M-ERWSM2032	M20	M32	22,0	7,0	35	50
M-ERWSM2532	M25	M32	22,0	7,5	35	25
M-ERWSM2540	M25	M40	24,0	7,5	43	25
M-ERWSM3240	M32	M40	25,0	8,0	43	20
M-ERWSM3250	M32	M50	28,0	8,0	54	20
M-ERWSM4050	M40	M50	28,0	8,0	54	10
M-ERWSM5063	M50	M63	33,0	10,0	65	10

M-ERW PG

Art. Nr. art. no.	AG male	IG female	L mm	GL / AG mm	AD mm	VPE Stk unit pcs.
M-ERWPG0709	PG07	PG09	15,0	5,0	17	100
M-ERWPG0911	PG09	PG11	16,5	6,0	20	100
M-ERWPG0913	PG09	PG13,5	17,5	6,0	22	100
M-ERWPG1113	PG11	PG13,5	17,5	6,0	22	100
M-ERWPG1116	PG11	PG16	19,0	6,5	24	100
M-ERWPG1121	PG11	PG21	21,0	6,5	30	100
M-ERWPG1316	PG13,5	PG16	19,0	6,5	24	100
M-ERWPG1321	PG13,5	PG21	21,0	6,5	30	100
M-ERWPG1621	PG16	PG21	21,0	6,5	30	100
M-ERWPG1629	PG16	PG29	22,5	6,5	39	50
M-ERWPG2129	PG21	PG29	23,0	7,0	39	50
M-ERWPG2936	PG29	PG36	27,5	8,0	50	25
M-ERWPG3642	PG36	PG42	31,0	9,0	57	10
M-ERWPG4248	PG42	PG48	33,0	10,0	64	10

M-ERWS Zoll / gas

Art. Nr. art. no.	AG male	IG female	L mm	GL / AG mm	SW mm	VPE Stk unit pcs.
M-ERWSZ014038	1/4"	3/8"	7,0	6,0	20	50
M-ERWSZ038012	3/8"	1/2"	9,0	6,0	24	50
M-ERWSZ012034	1/2"	3/4"	9,0	8,0	30	50
M-ERWSZ034100	3/4"	1"	9,0	8,0	35	50
M-ERWSZ034112	3/4"	1 1/2"	16,0	10,0	55	10
M-ERWSZ100114	1"	1 1/4"	12,0	11,0	45	10
M-ERWSZ100112	1"	1 1/2"	16,0	10,0	55	10
M-ERWSZ114112	1 1/4"	1 1/2"	12,0	11,0	51	10
M-ERWSZ112200	1 1/2"	2"	12,0	11,0	64	5
M-ERWSZ212300	2 1/2"	3"	25,0	20,0	-	5

L	Länge gesamt / overall length
GL	Gewindelänge / thread length
AG	Außengewinde / male thread
IG	Innengewinde / female thread
SW	Schlüsselweite / key-width
H	Höhe / height
ID	Innendurchmesser / inside diameter

