

M-N



Ausführung construction	Gewindenippel nipple
Werkstoff material	Messing vernickelt nickel-plated brass
Temperatur temperature	bis +200°C up to +200°C



metrisch / metric

Art. Nr. art. no.	AG male	L mm	ID mm	VPE Stk. unit pcs.
M-NM16	M16	22	12	20
M-NM20	M20	22	15	20
M-NM25	M25	25	20	20
M-NM32	M32	28	25	10
M-NM40	M40	38	34	5
M-NM50	M50	40	40	5
M-NM63	M63	46	57	5

PG

Art. Nr. art. no.	AG male	L mm	ID mm	VPE Stk. unit pcs.
M-NP001	PG07	16	9	20
M-NP002*	PG09	17	11	20
M-NP003	PG11	17	14	20
M-NP004	PG13,5	17	16	20
M-NP005	PG16	17	18	20
M-NP006	PG21	21	23	10
M-NP007	PG29	23	31	10
M-NP008	PG36	25	39	5
M-NP009*	PG42	28	45	2
M-NP010	PG48	31	53	2

Zoll / gas

Art. Nr. art. no.	AG male	L mm	ID mm	VPE Stk. unit pcs.
M-NG02	1/4"	19	9	20
M-NG03	3/8"	22	12	20
M-NG04*	1/2"	22	15	20
M-NG05*	3/4"	25	20	20
M-NG06*	1"	28	25	10
M-NG07*	1 1/4"	38	34	5
M-NG08*	1 1/2"	40	40	5
M-NG10*	2"	44	53	2
M-NG11*	2 1/2"	40	66	–
M-NG12*	3"	64	80	–

L	Länge gesamt / overall length
GL	Gewindelänge / thread length
AG	Außengewinde / male thread
IG	Innengewinde / female thread
SW	Schlüsselweite / key-width
H	Höhe / height
ID	Innendurchmesser / inside diameter