


M-VSK / X-VSK



Ausführung construction	Verschlussschraube plug
Werkstoff material	Messing vernickelt (M-VSK) nickel-plated brass (M-VSK)
Werkstoff material	Edelstahl V2A (X-VSK) stainless steel AISI304 (X-VSK)
Temperatur temperature	bis +200°C up to +200°C



metrisch / metric

Art. Nr. art. no.	AG male	GL mm	L mm	SW mm	VPE Stk. unit pcs.
M-VSKM16	M16	8	13	19	20
M-VSKM20	M20	8	13	22	20
M-VSKM25	M25	9	14	30	10
M-VSKM32	M32	9	14	35	10
M-VSKM40	M40	9	17	42	5
M-VSKM50	M50	13	23	55	5
M-VSKM63	M63	16	24	81	2

PG

Art. Nr. art. no.	AG male	GL mm	L mm	SW mm	VPE Stk. unit pcs.
M-VSKP07	PG07	8	12	14	20
M-VSKP09	PG09	8	12	17	20
M-VSKP11	PG11	8	13	20	20
M-VSKP13	PG13,5	9	14	22	20
M-VSKP16	PG16	9	14	24	20
M-VSKP21	PG21	10	15	30	10
M-VSKP29	PG29	10	15	38	10
M-VSKP36	PG36	13	20	50	5
M-VSKP42	PG42	12	21	55	5
M-VSKP48	PG48	15	25	60	2

Zoll / gas

Art. Nr. art. no.	AG male	GL mm	L mm	SW mm	VPE Stk. unit pcs.
M-VSKG014	1/4"	8	12,0	15	20
M-VSKG038	3/8"	8	13,0	19	20
M-VSG012	1/2"	9	14,0	24	20
M-VSKG034	3/4"	9	14,0	30	10
M-VSKG100	1"	10	15,5	38	10
M-VSKG114	1 1/4"	15	22,0	42	5
M-VSKG112	1 1/2"	15	22,0	50	5
M-VSKG200	2"	17	25,0	60	2
M-VSKG212	2 1/2"	19	29,0	75	2

metrisch inkl. O-Ring / metric // with O-Ring

Art. Nr. art. no.	AG male	GL mm	L mm	SW mm	VPE Stk. unit pcs.
X-VSKM16	M16	6,0	9	19	50
X-VSKM20	M20	6,5	9,5	22	50
X-VSKM25	M25	6,5	9,5	27	50
X-VSKM32	M32	7,0	10,5	36	50

PG inkl. O-Ring / PG // with O-Ring

Art. Nr. art. no.	AG male	GL mm	L mm	SW mm	VPE Stk. unit pcs.
X-VSKP07	PG07	5,0	8	14	50
X-VSKP09	PG09	6,0	8,8	17	50
X-VSKP11	PG11	6,0	9	22	50
X-VSKP13	PG13,5	6,0	9	22	50
X-VSKP16	PG16	6,5	9,5	24	50
X-VSKP21	PG21	7,0	10,5	30	50

L	Länge gesamt / overall length
GL	Gewindelänge / thread length
AG	Außengewinde / male thread
IG	Innengewinde / female thread
SW	Schlüsselweite / key-width
H	Höhe / height
ID	Innendurchmesser / inside diameter

