

# M-W45MR



**Ausführung**  
construction Winkel 45°  
elbow 45°

**Werkstoff**  
material Messing vernickelt  
nickled-plated brass



Art. Nr. art. no.	AG male	IG female	ID mm	L mm	GL mm	SW mm	VPE Stk. unit pcs.
M-W45MR16	M16	M16	11,5	-	10,0	-	50
M-W45MR20	M20	M20	15,0	-	10,0	-	50
M-W45MR25	M25	M25	20,0	-	10,0	-	50
M-W45MR32	M32	M32	27,0	-	10,0	-	50

Zubehör Metall / metal accessories

# M-W45



**Werkstoff**  
material Messing vernickelt  
nickel-plated brass



metrisch / metric

Art. Nr. art. no.	AG male	IG female	ID mm	L mm	GL mm	SW mm	VPE Stk. unit pcs.
M-W45M16	M16	M16	-	-	6,5	-	25
M-W45M20	M20	M20	-	-	7,5	-	25
M-W45M25	M25	M25	-	-	7,0	-	25
M-W45M32	M32	M32	-	-	8,5	-	10

PG

Art. Nr. art. no.	AG male	IG female	ID mm	L mm	GL mm	SW mm	VPE Stk. unit pcs.
M-W45P11	PG11	PG11	-	-	8,0	-	25
M-W45P16	PG16	PG16	-	-	10,0	-	25
M-W45P21	PG21	PG21	-	-	11,0	-	25
M-W45P29	PG29	PG29	-	-	8,0	-	10

# M-FVM



**Ausführung**  
construction Feststellvorrichtung  
coupling

**Werkstoff**  
material Messing vernickelt  
nickled-plated brass

**Temperatur**  
temperature -20°C - +100°C



Art. Nr. art. no.	AG male	IG female	ID mm	L mm	GL mm	SW mm	VPE Stk. unit pcs.
M-FVM16	M16	-	-	20	6	18	25
M-FVM20	M20	-	-	20,5	6,5	22	25
M-FVM25	M25	-	-	22	7	28	25
M-FVM32	M32	-	-	26	8	35	10
M-FVM40	M40	-	-	27	8	43	10

