

Ausführung construction	Gehäuse box
	LIG: mit Befestigungsbohrung with fixing wholes
	LIGO: ohne Befestigungsboh- rungen without fixing wholes
Werkstoff material	Edelstahl stainless steel
Dichtung sealing	PU
Temperatur temperature	-40°C - +90°C
Schutzart protection	IP66 / 68 / 69K

Art. Nr. LIG art. no. LIG	Art. Nr. LIGO art. no. LIGO	Länge mm length mm	Breite mm width mm	Höhe mm height mm	VPE Stk. unit pcs.
LIG100	LIGO100	100	100	61	1
LIG101	LIGO101	150	100	61	1
LIG150	LIGO150	150	150	81	1
LIG102	-	200	100	61	1
LIG200	LIGO200	200	200	81	1
LIG201	LIGO201	200	200	121	1
LIG151	-	300	150	81	1
LIG202	-	300	200	81	1
LIG203	LIGO203	300	200	121	1
LIG300	-	300	300	121	1
LIG301	-	300	300	161	1
LIG380	-	380	380	161	1
LIG152	-	400	150	81	1
LIG204	-	400	200	121	1
LIG302	-	400	300	161	1
LIG303	-	500	300	161	1
LIG400	-	500	400	161	1
LIG600	-	600	200	121	1



Weitere verfügbare Edelstahl-Gehäuse:

Typ LIGS: Industriegehäuse mit Scharnier (verfügbare Maße: 200x250x97 mm bis 600x380x217 mm)

Typ LKSS: Edelstahl-Kleinschaltschrank mit scharnierter Tür (verfügbare Maße: 200x300x155 mm bis 600x760x210 mm)

Weitere Größen und EMV-Ausführung auf Anfrage.

Weitere Dichtungen verfügbar: Polyurethan (PU)

Other available Stainless steel boxes:

Type LIGS: Industrial housing with hinge (available sizes: 200x250x97 mm to 600x380x217 mm)

Type LKSS: Stainless steel compact cabinet with hinged door (available sizes: 200x300x155 mm to 600x760x210 mm)

Additional sizes and emc-versions on request.

Other sealings also available: polyurethan (PU)

