

C2 / C2D / C2S / C4



Ausführung
construction Abzweigkasten
junction box


Werkstoff
material Aluguss
aluminium die cast

Dichtung
sealing TPE


Temperatur
temperature -40°C - +100°C

Schutzart
protection IP65


gemäß
according to IEC EN 61386




C2



C2D



C2S



C4

C2

Art. Nr. M art. no. M	metrisch metric	Art. Nr. PG art. no. PG	PG PG	Art. Nr. Zoll art. no. GAS	Zoll GAS	A mm	B mm	C mm	VPE Stk. unit pcs.
-	-	C24009	PG09	C204001	1/4"	82	35	46	10
C2400M16	M16	C240011	PG11	C204002	3/8"	82	35	46	10
C2410M20	M20	C241013	PG13,5	C204101	1/2"	115	45	59	10
-	-	C241016	PG16	-	-	115	45	59	10
C2410M25	M25	C241021	PG21	C204102	3/4"	115	45	59	10
C2420M32	M32	C242029	PG29	C20420	1"	128	55	76	5
C2430M40	M40	-	-	C204301	1 1/4"	146	70	95	5
C2430M50	M50	C243036	PG36	C204302	1 1/2"	146	70	95	5
-	-	C244048	PG48	C204402	2"	160	80	110	2
-	-	-	-	C20450	2 1/2"	276	110	136	1
-	-	-	-	C20460	3"	276	110	152	1

C2D

Art. Nr. M art. no. M	metrisch metric	Art. Nr. PG art. no. PG	PG PG	Art. Nr. Zoll art. no. GAS	Zoll GAS	A mm	B mm	C mm	VPE Stk. unit pcs.
-	-	C2D9009	PG09	C2D09001	1/4"	82	46	34	10
C2D900M16	M16	C2D90011	PG11	C2D09002	3/8"	82	46	34	10
C2D910M20	M20	C2D91013	PG13,5	C2D09101	1/2"	115	59	44	10
-	-	C2D91016	PG16	-	-	115	59	44	10
C2D910M25	M25	C2D91021	PG21	C2D09102	3/4"	115	59	44	10
C2D920M32	M32	C2D92029	PG29	C2D0920	1"	128	76	54	5
C2D930M40	M40	-	-	C2D09301	1 1/4"	146	95	70	5
C2D930M50	M50	C2D93036	PG36	C2D09302	1 1/2"	146	95	70	5
-	-	C2D94048	PG48	C2D09402	2"	160	110	80	2
-	-	-	-	C2D09050	2 1/2"	276	144	102	1
-	-	-	-	C2D09060	3"	276	144	118	1

C2S

Art. Nr. M art. no. M	metrisch metric	Art. Nr. PG art. no. PG	PG PG	Art. Nr. Zoll art. no. GAS	Zoll GAS	A mm	B mm	C mm	VPE Stk. unit pcs.
-	-	C2S10009	PG09	C2S010001	1/4"	82	46	34	10
C2S1000M16	M16	C2S100011	PG11	C2S010002	3/8"	82	46	34	10
C2S1010M20	M20	C2S101013	PG13,5	C2S010101	1/2"	115	59	44	10
-	-	C2S101016	PG16	-	-	115	59	44	10
C2S1010M25	M25	C2S101021	PG21	C2S010102	3/4"	115	59	44	10
C2S1020M32	M32	C2S102029	PG29	C2S01020	1"	128	76	54	5
C2S1030M40	M40	-	-	C2S010301	1 1/4"	146	95	70	5
C2S1030M50	M50	C2S103036	PG36	C2S010302	1 1/2"	146	95	70	5
-	-	C2S104048	PG48	C2S010402	2"	160	110	80	2
-	-	-	-	C2S01050	2 1/2"	276	144	102	1
-	-	-	-	C2S01060	3"	276	144	118	1

C4

Art. Nr. M art. no. M	metrisch metric	Art. Nr. PG art. no. PG	PG PG	Art. Nr. Zoll art. no. GAS	Zoll GAS	A mm	B mm	C mm	VPE Stk. unit pcs.
-	-	C46009	PG09	C406001	1/4"	94	57	34	10
C4600M16	M16	C460011	PG11	C406002	3/8"	94	57	34	10
C4610M20	M20	C461013	PG13,5	C406101	1/2"	130	74	44	10
-	-	C461016	PG16	-	-	130	74	44	10
C4610M25	M25	C461021	PG21	C406102	3/4"	130	74	44	10
C4620M32	M32	C462029	PG29	C40620	1"	150	97	54	5
C4630M40	M40	-	-	C406301	1 1/4"	170	120	70	5
C4630M50	M50	C463036	PG36	C406302	1 1/2"	170	120	70	5
-	-	C464048	PG48	C406402	2"	190	140	80	2
-	-	-	-	C40650	2 1/2"	310	178	102	1
-	-	-	-	C40660	3"	310	178	118	1

Gehäuse / boxes