

# K-EXe / K-EXi



ATEX

<b>Ausführung construction</b>	EXe
<b>Werkstoff material</b>	Polyamid 6 / CR / SI polyamide 6 / CR / SI
<b>Temperatur temperature</b>	-40°C - +70°C / CR
<b>Temperatur temperature</b>	-60°C - +70°C / SI
<b>Schutzart protection</b>	IP68
<b>Besonderheit specials</b>	EX-Zulassungen EX-approvals
<b>ATEX</b>	Ex II GD EX e IIC Gb / Ex tb IIIC Db IP66/68 EAC

## K-EXe

Art. Nr. CR art. no. CR	Art. Nr. SI art. no. SI	Gewinde thread	für Kabel for cable	SW1 mm	SW2 mm	GL mm	H mm	VPE Stk. unit pcs.
K-EXEM1206	K-EXEM1206SI	M12	4,0 - 6,5	15	15	10	22,0	100
K-EXEM1608	K-EXEM1608SI	M16	5,0 - 8,0	19	19	10	26,0	50
K-EXEM1610	K-EXEM1610SI	M16	6,0 - 10,0	22	22	10	29,5	50
K-EXEM2012	K-EXEM2012SI	M20	7,0 - 12,0	24	24	10	30,0	50
K-EXEM2013	K-EXEM2013SI	M20	7,0 - 13,0	25	25	10	30,0	50
K-EXEM2014	K-EXEM2014SI	M20	11,0 - 14,0	27	27	10	33,0	50
K-EXEM2517	K-EXEM2517SI	M25	12,0 - 17,0	29	29	10	34,0	50
K-EXEM2518	K-EXEM2518SI	M25	14,0 - 18,0	33	33	10	35,0	25
K-EXEM3221	K-EXEM3221SI	M32	16,0 - 21,0	36	36	10	42,0	25
K-EXEM3225	K-EXEM3225SI	M32	19,0 - 25,0	42	42	15	40,5	20
K-EXEM4028	K-EXEM4028SI	M40	20,0 - 28,0	46	46	10	45,0	20
K-EXEM4032	K-EXEM4032SI	M40	28,0 - 32,0	53	53	18	50,0	10
K-EXEM5038	K-EXEM5038SI	M50	31,0 - 38,0	60	60	18	54,0	10
K-EXEM6344	K-EXEM6344SI	M63	35,0 - 44,0	65	65	13	54,0	10

## K-EXi

Art. Nr. CR art. no. CR	Art. Nr. SI art. no. SI	Gewinde thread	für Kabel for cable	SW1 mm	SW2 mm	GL mm	H mm	VPE Stk. unit pcs.
K-EXIM1206	K-EXIM1206SI	M12	4,0 - 6,5	15	15	10	22,0	100
K-EXIM1608	K-EXIM1608SI	M16	5,0 - 8,0	19	19	10	26,0	50
K-EXIM1610	K-EXIM1610SI	M16	6,0 - 10,0	22	22	10	29,5	50
K-EXIM2012	K-EXIM2012SI	M20	7,0 - 12,0	24	24	10	30,0	50
K-EXIM2013	K-EXIM2013SI	M20	7,0 - 13,0	25	25	10	30,0	50
K-EXIM2014	K-EXIM2014SI	M20	11,0 - 14,0	27	27	10	33,0	50
K-EXIM2517	K-EXIM2517SI	M25	12,0 - 17,0	29	29	10	34,0	50
K-EXIM2518	K-EXIM2518SI	M25	14,0 - 18,0	33	33	10	35,0	25
K-EXIM3221	K-EXIM3221SI	M32	16,0 - 21,0	36	36	10	42,0	25
K-EXIM3225	K-EXIM3225SI	M32	19,0 - 25,0	42	42	15	40,5	20
K-EXIM4028	K-EXIM4028SI	M40	20,0 - 28,0	46	46	10	45,0	20
K-EXIM4032	K-EXIM4032SI	M40	28,0 - 32,0	53	53	18	50,0	10
K-EXIM5038	K-EXIM5038SI	M50	31,0 - 38,0	60	60	18	54,0	10
K-EXIM6344	K-EXIM6344SI	M63	35,0 - 44,0	65	65	13	54,0	10



K-EXe



K-EXi

