

DAR



Ausführung construction	Metallschlauch, doppelt verklammert, PVC-Ummantelung metal conduit, double seam, PVC-cover	
Werkstoff material	Stahl verzinkt PVC-Ummantelung galvanised steel PVC-cover	
Temperatur temperature	-20°C - +70°C	
Schutzart protection	IP68	
Gemäß according to	IEC EN 61386	
Passende Verschraubungen suitable fittings	CMMF	28
Seite page	CMMG	30
	CMF	31
	CMPR	32
	CMCC	34

Metallschlauch aus verzinktem Stahl, Agraffprofil
metal conduit made of galvanised steel, agraff profile



dicker und robuster PVC-Mantel
thick and robust PVC-cover

Eigenschaften
properties

flexibel - zugfest - hohe Scheiteldruckfestigkeit - flüssigkeitsdicht - selbstverlöschend - UV-beständig - flammwidrig
Agraffprofil - benzinbeständig - gute Ölbeständigkeit - gute Säurebeständigkeit - silikon- und cadmiumfrei
hohe Schlagfestigkeit - Internationale Zulassung
flexible - stretch resistant - high compressive strength - liquid tight - self extinguishing - UV-resistant - flame retardant
Agraff profile - petrol resistant - oil resistant - acid resistant - free of silicone and cadmium - high impact strength
international approval

Anwendungen
application

- Maschinenbau**
machine-building ✓
- Elektroinstallation**
electro-installation ✓
- Fahrzeugbau**
automotive ✓
- EMV-Anwendungen**
EMC-application
- Automation**
automation ✓
- Bahn**
railway
- Schiffsbau**
shipbuilding ✓
- EX-Anwendungen**
EX-application

Art. Nr. schw. art. no. black	Art. Nr. grau art. no. grey	Art. Nr. EX. art. no. EX.	NW DN	ID mm	AD mm OD mm	Biegeradius mm bending radius mm +/- 15 %	VPE unit
DAR010N	DAR010G	EXDAR010N	10	10,0	15,0	60	50m
DAR012N	DAR012G	EXDAR012N	12	12,0	17,0	70	50m
DAR013N	DAR013G	EXDAR013N	13	13,0	19,0	80	50m
DAR015N	DAR015G	EXDAR015N	15	15,5	21,0	90	50m
DAR018N	DAR018G	EXDAR018N	18	18,0	25,0	100	50m
DAR020N	DAR020G	EXDAR020N	20	20,5	27,0	120	50m
DAR025N	DAR025G	EXDAR025N	25	25,0	32,0	130	25m
DAR027N	DAR027G	EXDAR027N	27	26,5	34,0	140	25m
DAR033N	DAR033G	EXDAR033N	33	33,0	41,0	180	20m
DAR035N	DAR035G	EXDAR035N	35	35,0	43,0	190	20m
DAR040N	DAR040G	EXDAR040N	40	40,0	48,0	240	20m
DAR050N	DAR050G	EXDAR050N	50	50,5	58,5	300	20m
DAR065N	DAR065G	EXDAR065N	65	65,0	74,0	450	20m
DAR075N	DAR075G	EXDAR075N	75	75,0	84,0	500	20m
DAR100N	DAR100G	EXDAR100N	100	100,0	109,0	750	10m

Doppelte Verklammerung
double seam

