

**Ausführung**  
construction Steckrohre  
connecting pipes

**Werkstoff**  
material verzinkt / feuerverzinkt  
Edelstahl  
galvanised steel / hot dip  
galv. stainless steel

**Temperatur**  
temperature -60°C - +250°C  
-60°C - +600°C (V2A + V4A)

**Schutzart**  
protection IP67

**gemäß**  
according to IEC EN 61386

**galv. verzinkt**

Art. Nr. art. no.	Länge length	NW DN	AD mm OD mm	VPE unit
STR163	3 M	M16	16	30 M
STR203	3 M	M20	20	30 M
STR253	3 M	M25	25	15 M
STR323	3 M	M32	32	15 M
STR403	3 M	M40	40	9 M
STR503	3 M	M50	50	6 M
STR603	3 M	-	60	6 M
STR633	3 M	M63	63	6 M

**V2A**

Art. Nr. art. no.	Länge length	NW DN	AD mm OD mm	VPE unit
STRX163	3 M	M16	16	30 M
STRX203	3 M	M20	20	30 M
STRX253	3 M	M25	25	15 M
STRX323	3 M	M32	32	15 M
STRX403	3 M	M40	40	9 M
STRX503	3 M	M50	50	6 M
STRX603	3 M	-	60	6 M
STRX633	3 M	M63	63	6 M

**feuerverzinkt**

Art. Nr. art. no.	Länge length	NW DN	AD mm OD mm	VPE unit
STRF163	3 M	M16	16	30 M
STRF203	3 M	M20	20	30 M
STRF253	3 M	M25	25	15 M
STRF323	3 M	M32	32	15 M
STRF403	3 M	M40	40	9 M
STRF503	3 M	M50	50	6 M
STRF633	3 M	M63	63	6 M

**V4A**

Art. Nr. art. no.	Länge length	NW DN	AD mm OD mm	VPE unit
STRX163V4A	3 M	M16	16	30 M
STRX203V4A	3 M	M20	20	30 M
STRX253V4A	3 M	M25	25	15 M
STRX323V4A	3 M	M32	32	15 M
STRX403V4A	3 M	M40	40	9 M
STRX503V4A	3 M	M50	50	6 M
STRX603V4A	3 M	-	60	6 M
STRX633V4A	3 M	M63	63	6 M

**Eigenschaften**  
Starres Rohr für die Elektroinstallation gemäß  
IEC EN 61836.

**Properties**  
Rigid pipe for electro-installation according to  
IEC EN 61836.

