


Mainfix MGAG-Q



Mainfix Metall / Mainfix metal

Ausführung construction	starrs Außengewinde rigid male thread
Werkstoff material	Messing vernickelt nickel-plated brass
Temperatur temperature	-40°C - +200°C
Schutzart protection	IP 40
gemäß according to	IEC EN 61386



Gewinde metrisch / thread metric

Art. Nr. art. no.	Gewinde thread	Schlauch NW conduit DN	SW1 mm	GL mm	ID mm	VPE Stk. unit pcs.
MGAG10M16Q	M16	10	19	8,5	20	20
MGAG12M16Q	M16	12	19	10,0	20	20
MGAG12M20Q	M20	12	24	10,0	20	20
MGAG13M20Q	M20	13	24	11,5	20	20
MGAG15M20Q	M20	15	24	14,0	20	20
MGAG20M25Q	M25	20	28	18,5	10	20
MGAG21M25Q	M25	21	28	19,5	10	20
MGAG25M32Q	M32	25	36	23,0	10	20
MGAG28M32Q	M32	28	36	26,0	10	10
MGAG37M40Q	M40	37	45	35,0	5	10
MGAG45M50Q	M50	45	55	41,5	5	10
MGAG52M63Q	M63	52	64	48,5	5	5

Gewinde Zoll / thread gas

Art. Nr. art. no.	Gewinde thread	Schlauch NW conduit DN	SW1 mm	GL mm	ID mm	VPE Stk. unit pcs.
MGAG07Q	1/4"	7	15	5,5	20	20
MGAG09Q	1/4"	8,5	15	7,0	20	20
MGAG10Q	1/4"	10	19	8,5	20	20
MGAG10AQ	3/8"	10	19	8,5	20	20
MGAG12Q	3/8"	12	19	10,0	20	20
MGAG13Q	1/2"	13	24	11,5	20	20
MGAG15Q	1/2"	15	24	14,0	20	20
MGAG20Q	3/4"	20	28	18,5	10	20
MGAG21Q	3/4"	21	28	19,5	10	20
MGAG25Q	1"	25	36	23,0	10	20
MGAG28Q	1"	28	36	26,0	10	20
MGAG37Q	1 1/4"	37	45	35,0	5	10
MGAG45Q	1 1/2"	45	55	41,5	5	10
MGAG52Q	2"	52	64	48,5	5	10

Passende Schläuche suitable conduits



alle Metallschläuche
all metal conduits



alle Metallschläuche mit dünnem Mantel
all metal conduits with thin cover

Passendes Zubehör suitable accessoires



EESO



EES

