

CMMG



Ausführung construction	drehbares Außengew. swivelling male thread
Werkstoff material	Messing vernickelt nickel-plated brass
Temperatur temperature	-40°C - +105°C
Schutzart protection	IP 67
Gemäß according to	IEC EN 61386

Für Schlauchtyp for conduit type	L	16
	DAR	17
Seite page	DARX	18
	LPU	19
	DAPU	19
	T	10
	TP	11
	SVT	14
	SVPEVAT	15
	LHT	20



Gewindeart metrisch

Art. Nr. art. no.	Gewinde thread	Schlauch NW conduit DN	SW1 mm	SW2 mm	SW3 mm	GL mm	ID mm	VPE Stk. unit pcs.
CMMG09M12	M12	8,5	15	20	22	9	7,0	20
CMMG09M16	M16	8,5	19	20	22	9	7,0	20
CMMG09M20	M20	8,5	22	22	22	9	7,0	20
CMMG10M12	M12	10	15	22	24	9	7,0	20
CMMG10M16	M16	10	19	22	24	9	8,5	20
CMMG10M20	M20	10	24	22	24	9	8,5	20
CMMG12M16	M16	12	19	24	26	9	10,0	20
CMMG12M20	M20	12	24	24	26	9	10,0	20
CMMG13M16	M16	13	19	26	28	9	10,0	20
CMMG13M20	M20	13	24	26	28	9	10,0	20
CMMG15M20	M20	15	24	28	30	9	14,0	20
CMMG15M25	M25	15	30	28	30	10	13,8	20
CMMG18M20	M20	18	24	32	34	9	14,0	10
CMMG18M25	M25	18	30	32	34	10	16,5	10
CMMG20M25	M25	20	30	35	38	10	18,0	10
CMMG20M32	M32	20	38	35	38	13	18,0	10
CMMG25M32	M32	25	38	40	42	13	23,0	10
CMMG27M32	M32	27	38	42	45	13	24,0	10
CMMG33M40	M40	33	45	50	53	18	31,0	5
CMMG35M40	M40	35	45	50	53	18	33,0	5
CMMG40M50	M50	40	52	58	61	20	37,5	5
CMMG50M63	M63	50	64	70	74	24	48,0	2

Gewindeart PG

Art. Nr. art. no.	Gewinde thread	Schlauch NW Conduit DN	SW1 mm	SW2 mm	SW3 mm	GL mm	ID mm	VPE Stk. unit pcs.
CMMGP09PG07	PG07	8,5	15	20	22	9	7,0	20
CMMGP09PG09	PG09	8,5	17	20	22	7	7,0	20
CMMGP09PG11	PG11	8,5	20	20	22	7	7,0	20
CMMGP09PG13	PG13,5	8,5	22	22	22	7	7,0	20
CMMGP10PG07	PG07	10	15	22	24	9	7,0	20
CMMGP10PG09	PG09	10	17	22	24	7	7,0	20
CMMGP10PG11	PG11	10	20	22	24	7	8,5	20
CMMGP10PG13	PG13,5	10	22	22	24	7	8,5	20
CMMGP10PG16	PG16	10	24	22	24	7	8,5	20
CMMGP12PG11	PG11	12	20	24	26	7	10,0	20
CMMGP12PG13	PG13,5	12	22	24	26	7	10,0	20
CMMGP12PG16	PG16	12	24	24	26	7	10,0	20
CMMGP13PG11	PG11	13	20	26	28	7	10,0	20
CMMGP13PG13	PG13,5	13	22	26	28	7	10,0	20
CMMGP13PG16	PG16	13	24	26	28	7	10,0	20
CMMGP15PG13	PG13,5	15	24	28	30	10	14,0	20
CMMGP15PG16	PG16	15	24	28	30	10	14,0	20
CMMGP15PG21	PG21	15	30	28	30	10	14,0	20
CMMGP18PG13	PG13,5	18	24	32	34	10	14,0	10
CMMGP18PG16	PG16	18	24	32	34	10	14,0	10
CMMGP18PG21	PG21	18	30	32	34	10	16,5	10
CMMGP20PG21	PG21	20	30	35	38	10	18,5	10
CMMGP25PG29	PG29	25	38	40	42	12,5	23,0	10
CMMGP27PG29	PG29	27	38	42	45	12,5	24,0	10
CMMGP33PG36	PG36	33	45	50	53	18,5	31,0	5
CMMGP35PG36	PG36	35	45	50	53	18,5	32,5	5
CMMGP40PG36	PG36	40	52	58	61	20	37,5	5
CMMGP40PG42	PG42	40	58	58	61	20	37,5	5
CMMGP50PG48	PG48	50	65	70	74	24,5	48,0	2

Auf Anfrage
on requestWeitere Gewindearten (NPT / GAS)
further thread types (NPT / GAS) ✓Weitere Materialien (Edelstähle)
further materials (stainless steel) ✓