

TM



Ausführung construction	Standardprofil, mittelschwer standard profile, medium heavy	
Werkstoff material	Polyamid 6 (PA6) UL94 HB polyamide 6 (PA6) UL 94 HB	
Temperatur temperature	-40°C - +120°C kurzz. / short term +150°C	
Schutzart protection	IP68	
gemäß according to	IEC EN 61386	
Passende Verschraubungen suitable fittings	JAW-FIT-System	ab Seite 60
Seite page		

Wellrohr PA6, schwarz oder grau
corrugated conduit PA6, black or grey



Eigenschaften properties

flexibel - hohe Scheiteldruckfestigkeit - flüssigkeitsdicht - selbstverlöschend - UV-beständig - halogenfrei
benzinbeständig - gute Ölbeständigkeit - gute Säurebeständigkeit - silikon- und cadmiumfrei - internationale Zulassung
flexible - high compressive strength - liquid tight - self extinguishing - UV-resistant - free of halogene - flame retardant
petrol resistant - oil resistant - acid resistant - free of silicone and cadmium - international approval

Anwendungen application

Maschinenbau
machine-building ✓
Automation
automation ✓

Elektroinstallation
electro-installation ✓
Bahn
railway

Fahrzeugbau
automotive ✓
Schiffsbau
shipbuilding ✓

EMV-Anwendungen
EMC-application
EX-Anwendungen
EX-application

Art. Nr. schwarz art. no. black	Art. Nr. grau art. no. grey	NW DN	ID mm	AD mm OD mm	Biegeradius mm bending radius mm	VPE unit
TM004B	TM004G	4,5	4,3	7,3	8	100m
TM007B	TM007G	7	6,7	10,0	13	50m
TM008B	TM008G	8,5	8,4	11,7	15	50m
TM010B	TM010G	10	9,9	13,0	20	50m
TM012B	TM012G	12	12,2	15,7	30	50m
TM013B	TM013G	13	12,7	15,8	35	50m
TM014B	TM014G	14	14,2	18,5	40	50m
TM016B	TM016G	16	14,9	18,9	40	50m
TM017B	TM017G	17	16,6	21,2	45	50m
TM019B	TM019G	19	19,3	24,3	45	50m
TM022B	TM022G	22	21,2	25,5	50	50m
TM023B	TM023G	23	23,2	28,3	55	50m
TM026B	TM026G	26	25,7	32,2	60	50m
TM029B	TM029G	29	29,0	34,5	65	25m
TM036B	TM036G	36	36,0	42,4	90	25m
TM048B	TM048G	50	48,1	53,8	100	25m
TM056B	TM056G	56	56,3	67,2	130	30m
TM065B	TM065G	65	62,7	73,5	145	25m
TM070B	TM070G	70	67,5	80,0	160	10m
TM095B	TM095G	95	91,5	106,0	210	10m