

TP



Ausführung construction	Standardprofil, mittelschwer standard profile, medium heavy	
Werkstoff material	Polyamid 6 (PA6) UL94 V0 polyamide 6 (PA6) UL94 V0	
Temperatur temperature	-40°C - +120°C kurzz. / short term +150°C	
Schutzart protection	IP68	
gemäß according to	IEC EN 61386	
Passende Verschraubungen suitable fittings Seite page	JAW-FIT-System	ab Seite 60

Wellrohr PA6, schwarz oder grau
corrugated conduit PA6, black or grey



Eigenschaften properties

flexibel - hohe Scheiteldruckfestigkeit - flüssigkeitsdicht - selbstverlöschend - UV-beständig - halogenfrei - flammwidrig
benzinbeständig - gute Ölbeständigkeit - gute Säurebeständigkeit - silikon- und cadmiumfrei - internationale Zulassung
flexible - high compressive strength - liquid tight - self extinguishing - UV-resistant - free of halogene - flame retardant
petrol resistant - oil resistant - acid resistant - free of silicone and cadmium - international approval

Anwendungen application

Maschinenbau
machine-building ✓
Automation
automation ✓

Elektroinstallation
electro-installation ✓
Bahn
railway ✓

Fahrzeugbau
automotive ✓
Schiffsbau
shipbuilding ✓

EMV-Anwendungen
EMC-application
EX-Anwendungen
EX-application

Art. Nr. schwarz art. no. black	Art. Nr. grau art. no. grey	NW DN	ID mm	AD mm OD mm	Biegeradius mm bending radius mm	VPE unit
TP007B	TP007G	7	6,7	10,0	13	50m
TP008B	TP008G	8,5	8,4	11,7	15	50m
TP010B	TP010G	10	9,9	13,0	20	50m
TP012B	TP012G	12	12,2	15,7	30	50m
TP013B	TP013G	13	12,7	15,8	35	50m
TP014B	TP014G	14	14,2	18,5	40	50m
TP016B	TP016G	16	14,9	18,9	40	50m
TP017B	TP017G	17	16,6	21,2	45	50m
TP022B	TP022G	22	21,2	25,5	50	50m
TP023B	TP023G	23	23,2	28,3	55	50m
TP026B	TP026G	26	25,7	32,2	60	50m
TP029B	TP029G	29	29,0	34,5	65	25m
TP036B	TP036G	36	36,0	42,4	90	25m
TP048B	TP048G	50	48,1	53,8	100	25m