

Mainflex TWINCOR PA



Ausführung
construction Standardprofil, mittelschwer, teilbar standard profile, medium heavy, separable

Werkstoff
material PA6 UL94 V2

Temperatur
temperature -45°C - +120°C

kurzzeitig
short term +150°C

Schutzart
protection IP54

gemäß
according to IEC EN 61386



Twincor PA - SPLIT

	Art. Nr. schwarz art. no. black	Art. Nr. grau art. no. grey	NW DN	ID mm	AD mm OD mm	VPE unit
	TWCS07PA	a.A.	7	6,3	10	50m
	TWCS10PA	a.A.	10	8,8	13,5	50m
	TWCS14PA	a.A.	14	13,2	18,7	50m
	TWCS17PA	a.A.	17	16	21,5	50m
	TWCS20PA	a.A.	20	20,2	25,7	50m
	TWCS23PA	a.A.	23	23,9	31,3	50m
	TWCS29PA	a.A.	29	27,3	35,5	50m
	TWCS37PA	a.A.	37	32,5	43,2	25m
	TWCS48PA	a.A.	48	43,1	54,2	25m
	TWCS70PA	a.A.	70	67	79,8	10 / 25m
	TWCS100PA	a.A.	100	87,5	102,5	10m

Twincor PA - FIT

	Art. Nr. schwarz art. no. black	Art. Nr. grau art. no. grey	NW DN	ID mm	AD mm OD mm	VPE unit
	TWCF07PA	a.A.	7	6,2	11,2	50m
	TWCF10PA	a.A.	10	7,9	12,9	50m
	TWCF12PA	a.A.	12	10,3	15,8	50m
	TWCF17PA	a.A.	17	13,9	21	50m
	TWCF23PA	a.A.	23	20,5	28,3	50m
	TWCF29PA	a.A.	29	26,6	34,5	25m
	TWCF36PA	a.A.	36	32	41,8	25m
	TWCF48PA	a.A.	48	44	54,2	25m

Eigenschaften

TWINCOR - SPLIT: Abmessungen sind kompatibel mit allen teilbaren Mainfix Kunststoffverschraubungen.
TWINCOR - SPLIT: Dimensions are compatible with all divisible Mainfix plastic fittings.
TWINCOR - FIT: Abmessungen sind kompatibel mit allen Mainfix Kunststoffverschraubungen.
TWINCOR - FIT: Dimensions are compatible with all Mainfix plastic fittings.

Properties

Corrugated conduit for retrofit application of efficient protection. The re-closable double shell conduit properly overlaps and provides enhanced cable protection capabilities against external influences and impacts. Pre-assembled cable harnesses with already installed connectors can be accomplished easily and safe. This divisible conduit type made of Polyamide 6 perfectly suits various industrial application needs.

