

Ausführung
construction

starres Innengewinde
rigid female thread

Werkstoff
material

Polyamid 6, UL94 V0,
Messing vernickelt
polyamide 6, UL 94 V0,
nickel-plated brass

Temperatur
temperature

-40°C - +105°C

kurzzeitig
short term


+150°C

Schutzart
protection

IP68 / IP69K

gemäß
according to

IEC EN 61386



metrisch / metric

Art. Nr. schwarz art. no. black	Gewinde thread	NW DN	ID mm	GL mm	SW mm	L mm	VPE Stk. unit pcs.
MSF8B07M12	M12	7	9,0	8	15	35	100
MSF8B10M16	M16	10	11,6	11	20	39,4	50
MSF8B12M16	M16	12	12,5	11	22	43	50
MSF8B17M20	M20	17	18,0	11,5	26	44,35	50
MSF8B23M25	M25	23	23,0	11,5	30	53,5	30
MSF8B23M32	M32	23	26,0	11,5	38	53,5	30
MSF8B29M32	M32	29	29,5	11,5	38	55	20
MSF8B29M40	M40	29	29,5	11,5	44	55	20
MSF8B36M40	M40	36	36,5	11,5	45	63	20
MSF8B48M50	M50	48	48,0	15,5	58	73,5	10
MSF8B48M63	M63	48	48,5	18,0	70	76,5	10

PG

Art. Nr. art. no.	Gewinde thread	NW DN	ID mm	GL mm	SW mm	L mm	VPE Stk. unit pcs.
MSF8B07P07	PG7	7	7,1	9,0	17	37,5	100
MSF8B10P07	PG7	10	7,1	9,0	17	38,9	50
MSF8B10P09	PG9	10	10,1	9,0	20	39,4	50
MSF8B12P11	PG11	12	11,5	9,6	24	43,2	50
MSF8B12P13	PG13,5	12	13,5	9,5	26	43,1	50
MSF8B17P13	PG13,5	17	13,5	9,5	26	44,3	50
MSF8B17P13	PG16	17	16,2	9,0	27	43,3	50
MSF8B23P21	PG21	23	21,0	11,0	34	57,0	30
MSF8B23P29	PG29	23	26,0	13,0	42	59,5	30
MSF8B29P29	PG29	29	29,2	13,0	42	59,5	20
MSF8B36P36	PG36	36	37,8	13,5	55	68,0	20
MSF8B48P48	PG48	48	47,0	15,0	70	76,5	10

Die Innengewinde-Verschraubung des Typ SF ist mit PG und metrischen ISO-Metallgewinde erhältlich. Die Metallgewinde erreichen höchste Dauer-Verbindungsfestigkeiten und können optimal auch mit adhäsiven Gewindesicherungsmitteln versehen werden.

Sie eignen sich für normale Anforderungen in technischen oder Elektroinstallations-Anwendungen, aber auch für erhöhte Anforderungen in Industrie und Bahntechnik bei gleichzeitiger Abdichtung über das Wellrohr von bis zu IP69K.

Female fitting, type SF with PG and ISO metric metal thread. Metal thread ensure best possible thread connection strength and can also be efficiently and durably secured with standard adhesives.

The standard swiveling thread is suitable for use in mechanical engineering, vehicle construction, shipbuilding and railway technology and complies the protection class until IP69K.

