


# Mainfix BN

<b>Ausführung</b> construction	Bogen 90°, starres Außengewinde elbow 90°, rigid male thread
<b>Werkstoff</b> material	Polyamid 6, UL94 V0 polyamide 6, UL94 V0
<b>Temperatur</b> temperature	-40°C - +105°C
<b>kurzzeitig</b> short term	+150°C
<b>Schutzart</b> protection	IP66
<b>gemäß</b> according to	IEC EN 61386



## metrisch / metric

Art. Nr. IP66 art. no. IP66	Gewinde thread	NW DN	ID mm	GL mm	SW mm	L mm	VPE Stk. unit pcs.
BN6*07M12	M12	7	6,5	11	9,5	58,5	100
BN6*10M12	M12	10	6,5	11	9,5	59,5	100
BN6*10M16	M16	10	10,0	11	13,0	61,5	100
BN6*12M16	M16	12	10,0	11	14,0	64,0	100
BN6*12M20	M20	12	12,0	11	15,0	67,0	100
BN6*17M20	M20	17	13,8	12	17,0	75,0	50
BN6*23M25	M25	23	18,0	12	22,0	88,5	30
BN6*29M32	M32	29	23,7	13	28,0	100,3	20
BN6*36M40	M40	36	31,8	15	36,0	122,8	20
BN6*36M50	M50	36	36,0	15	40,0	127,5	20
BN6*48M50	M50	48	39,8	15	46,0	139,7	10
BN6*48M63	M63	48	47,8	15	55,0	144,0	10

## PG

Art. Nr. IP66 art. no. IP66	Gewinde thread	NW DN	ID mm	GL mm	SW mm	L mm	VPE Stk. unit pcs.
BN6*07P07	PG7	7	6,5	11	9,5	58,5	100
BN6*07P09	PG9	7	6,5	11	9,5	59,5	100
BN6*07P11	PG11	7	6,5	11	9,5	61,0	100
BN6*07P13	PG13,5	7	6,5	11	9,5	62,5	100
BN6*10P07	PG7	10	6,5	11	9,5	59,5	100
BN6*10P09	PG9	10	10,0	11	13,0	60,5	100
BN6*10P11	PG11	10	10,0	11	13,0	62,0	100
BN6*10P13	PG13,5	10	10,0	11	13,0	63,5	100
BN6*12P09	PG9	12	10,0	11	14,0	63,0	100
BN6*12P11	PG11	12	12,0	11	15,0	64,4	100
BN6*12P13	PG13,5	12	12,0	11	15,0	66,0	100
BN6*17P13	PG13,5	17	13,8	12	17,0	75,0	50
BN6*17P16	PG16	17	16,4	12	20,0	76,0	50
BN6*23P21	PG21	23	21,7	12	26,0	90,0	30
BN6*29P29	PG29	29	29,1	13	32,0	102,8	20
BN6*36P36	PG36	36	36,0	13	40,0	125,0	20
BN6*48P48	PG48	48	47,8	13	55,0	144,0	10

90°-Steck-Verschraubung mit Kunststoff-Außengewinde aus hochwertigem, speziell formuliertem Polyamid. Das Material ist selbstverlöschend, cadmium-, phosphor und halogenfrei sowie schlagfest und sehr gut beständig gegen chemische Stoffe. Extrem stoß- und chemikalienbeständig. Geeignet für industrielle und elektrotechnische Installations-Anwendungen sowie für erhöhte Anforderungen in schweren Industrie- und Eisenbahnanwendungen.

90°-elbow fitting with plastic male thread are manufactured from high-grade, specially formulated polyamides. These polyamides are self-extinguishing, free of halogen, phosphor and cadmium. Suitable for industrial and electro technical installation-applications as well as for increased requirements in heavy industry and railway applications and is also used in switch cupboard as conduit terminal.

