

Mainfix PC

EN 45545-2 (HL2)




Ausführung construction	Verbinder connector
Werkstoff material	Polyamid 6, UL94 V0 polyamide 6, UL94 V0
Temperatur temperature	-40°C - +105°C
Schutzart protection	IP68 / IP69K
gemäß according to	IEC EN 61386


Art. Nr. IP68/69K art. no. IP68/69K	NW DN	Rohr STD pipe STD	ID mm	L mm	VPE Stk. unit pcs.
PC8*1216	12	16	14,0	60,6	50
PC8*1720	17	20	18,0	61,8	50
PC8*2325	23	25	22,5	72,0	30
PC8*2932	29	32	29,5	72,5	20
PC8*3640	36	40	37,5	86,0	20
PC8*4850	48	50	47,5	92,5	10

Der praktische **Rohrverbinder Typ PC** für den raschen und sicheren Anschluss von Wellrohren mit starren Rohren ist geeignet für normale Anforderungen in technischen oder Elektroinstallations-Anwendungen, aber auch für erhöhte Anforderungen in Industrie und Bahntechnik bei gleichzeitiger Abdichtung über das Wellrohr von bis zu IP69K.

The **pipe connector type PC** with metal adapter provide practical, economic and secure connections rigid pipes, reducing time of installation suit with standard requirements in industrial and electro technical installation applications as well as for increased requirements in heavy industry and railway applications also provide complementary liquid and tightness at the conduit itself until to IP69K..



PC



Mainfix Kunststoff / Mainfix plastic