

# Mainfix MSS




Mainfix PVC

<b>Ausführung</b> construction	Schlauchanschlussstutzen mit starrem Außen-gewinde conduit nozzle with rigid male thread
<b>Werkstoff</b> material	Messing vernickelt nickel-plated brass
<b>Temperatur</b> temperature	-20°C - +105°C
<b>Schutzart</b> protection	IP67
<b>gemäß</b> according to	IEC EN 61386

## metrisch / metric

Art. Nr. art. no.	Gewinde thread	Schlauch NW conduit DN	SW mm	GL mm	ID mm	VPE Stk. unit pcs.
MSS10M12	M12	10	19	7	8	20
MSS10M16	M16	10	19	7	8	20
MSS12M16	M16	12	22	10	10	20
MSS12M20	M20	12	24	10	10	20
MSS15M20	M20	15	24	10	13	20
MSS20M20	M20	20	27	10	16	10
MSS20M25	M25	20	30	12	17	10
MSS27M25	M25	27	36	12	21	10
MSS27M32	M32	27	36	12	23	10
MSS36M32	M32	36	44	12	26	5
MSS40M40	M40	40	50	13	35	5
MSS47M50	M50	47	58	15	42	5
MSS58M63	M63	50	70	15	51	2



## PG

Art. Nr. art. no.	Gewinde thread	Schlauch NW conduit DN	SW1 mm	GL mm	ID mm	VPE Stk. unit pcs.
MSSP10PG07	PG07	10	19	7	8	20
MSSP10PG09	PG09	10	19	7	8	20
MSSP10PG11	PG11	10	22	7	8	20
MSSP12PG11	PG11	12	22	7	10	20
MSSP12PG13	PG13,5	12	24	7	10	20
MSSP12PG16	PG16	12	24	7	10	20
MSSP15PG13	PG13,5	15	24	7	13	20
MSSP15PG16	PG16	15	24	7	13	20
MSSP20PG13	PG13,5	20	27	7	16	10
MSSP20PG16	PG16	20	27	7	17	10
MSSP20PG21	PG21	20	30	10	17	10
MSSP27PG21	PG21	27	36	10	23	10
MSSP27PG29	PG29	27	40	10	23	10
MSSP36PG29	PG29	36	45	11	30	10
MSSP40PG36	PG36	40	50	13	36	5
MSSP47PG36	PG36	47	58	15	40	5
MSSP47PG42	PG42	47	58	15	42	5
MSSP58PG48	PG48	58	70	15	51	2

Messing Schlauchstutzen mit starrem Aussenge-winde, für alle Kunststoffschläuche.

Conduit nozzle made of nickel-plated-brass with rigid male thread for all plastic conduits.

