



EXCMMG



Ausführung construction	drehbares Außengew. swivelling male thread
Werkstoff material	Messing vernickelt nickel-plated brass
Temperatur temperature	-40°C - +105°C
Schutzart protection	IP 67
Gemäß according to	IEC EN 61386



II 2G Ex e IIC Gb
II 2D Ex tb IIIC Db IP67

Für Schlauchtyp
for conduit type

L
DAR
DARX
LPU
DAPU
T
TP
SVT
LVPEVAT
LHT



Gewindeart metrisch

Art. Nr. art. no.	Gewinde thread	Schlauch NW conduit DN	SW1 mm	SW2 mm	SW3 mm	GL mm	ID mm	VPE Stk. unit pcs.
EXCMMG09M12	M12	8,5	15	20	22	9	7,0	20
EXCMMG09M16	M16	8,5	19	20	22	9	7,0	20
EXCMMG09M20	M20	8,5	22	22	22	9	7,0	20
EXCMMG10M12	M12	10	15	22	24	9	7,0	20
EXCMMG10M16	M16	10	19	22	24	9	8,5	20
EXCMMG10M20	M20	10	24	22	24	9	8,5	20
EXCMMG12M16	M16	12	19	24	26	9	10,0	20
EXCMMG12M20	M20	12	24	24	26	9	10,0	20
EXCMMG13M16	M16	13	19	26	28	9	10,0	20
EXCMMG13M20	M20	13	24	26	28	9	10,0	20
EXCMMG15M20	M20	15	24	28	30	9	14,0	20
EXCMMG15M25	M25	15	30	28	30	10	13,8	20
EXCMMG18M20	M20	18	24	32	34	9	14,0	10
EXCMMG18M25	M25	18	30	32	34	10	16,5	10
EXCMMG20M25	M25	20	30	35	38	10	18,0	10
EXCMMG20M32	M32	20	38	35	38	13	18,0	10
EXCMMG25M32	M32	25	38	40	42	13	23,0	10
EXCMMG27M32	M32	27	38	42	45	13	24,0	10
EXCMMG33M40	M40	33	45	50	53	18	31,0	5
EXCMMG35M40	M40	35	45	50	53	18	33,0	5
EXCMMG40M50	M50	40	52	58	61	20	37,5	5
EXCMMG50M63	M63	50	64	70	74	24	48,0	2

Gewindeart PG

Art. Nr. art. no.	Gewinde thread	Schlauch NW Conduit DN	SW1 mm	SW2 mm	SW3 mm	GL mm	ID mm	VPE Stk. unit pcs.
EXCMMGP09PG07	PG07	8,5	15	20	22	9	7,0	20
EXCMMGP09PG09	PG09	8,5	17	20	22	7	7,0	20
EXCMMGP09PG11	PG11	8,5	20	20	22	7	7,0	20
EXCMMGP09PG13	PG13,5	8,5	22	22	22	7	7,0	20
EXCMMGP10PG07	PG07	10	15	22	24	9	7,0	20
EXCMMGP10PG09	PG09	10	17	22	24	7	7,0	20
EXCMMGP10PG11	PG11	10	20	22	24	7	8,5	20
EXCMMGP10PG13	PG13,5	10	22	22	24	7	8,5	20
EXCMMGP10PG16	PG16	10	24	22	24	7	8,5	20
EXCMMGP12PG11	PG11	12	20	24	26	7	10,0	20
EXCMMGP12PG13	PG13,5	12	22	24	26	7	10,0	20
EXCMMGP12PG16	PG16	12	24	24	26	7	10,0	20
EXCMMGP13PG11	PG11	13	20	26	28	7	10,0	20
EXCMMGP13PG13	PG13,5	13	22	26	28	7	10,0	20
EXCMMGP13PG16	PG16	13	24	26	28	7	10,0	20
EXCMMGP15PG13	PG13,5	15	24	28	30	10	14,0	20
EXCMMGP15PG16	PG16	15	24	28	30	10	14,0	20
EXCMMGP15PG21	PG21	15	30	28	30	10	14,0	20
EXCMMGP18PG13	PG13,5	18	24	32	34	10	14,0	10
EXCMMGP18PG16	PG16	18	24	32	34	10	14,0	10
EXCMMGP18PG21	PG21	18	30	32	34	10	16,5	10
EXCMMGP20PG21	PG21	20	30	35	38	10	18,5	10
EXCMMGP25PG29	PG29	25	38	40	42	12,5	23,0	10
EXCMMGP27PG29	PG29	27	38	42	45	12,5	24,0	10
EXCMMGP33PG36	PG36	33	45	50	53	18,5	31,0	5
EXCMMGP35PG36	PG36	35	45	50	53	18,5	32,5	5
EXCMMGP40PG36	PG36	40	52	58	61	20	37,5	5
EXCMMGP40PG42	PG42	40	58	58	61	20	37,5	5
EXCMMGP50PG48	PG48	50	65	70	74	24,5	48,0	2

Auf Anfrage
on request

Weitere Gewindearten (NPT / GAS)
further thread types (NPT / GAS) ✓

Weitere Materialien (Edelstähle)
further materials (stainless steel) ✓