

EXLA



Ausführung construction	Gehäuse enclosure
Werkstoff material	Aluminium aluminium
Dichtung sealing	PU
Temperatur temperature	-40°C - +90°C°
Schutzart protection	IP66 / 68 / 69K
Gemäß according to	-



II 2G Ex e IIC T6/T5/T4 Gb
 II 2G EX ia IIC T6/T5T4 Gb
 II 2G Ex d e ia mb IIC T6/T5/T4 Gc
 II 3G Ex e d mb ia nA nC IIC T6/T5/T4 Gc
 II 2D Ex tb IIIC T85°C/T100°C/T135°C Db IP66



Art. Nr. LA art. no. LA	Länge mm length mm	Breite mm width mm	Höhe mm height mm	VPE Stk. unit pcs.
EXLA60	58	64	34	1
EXLA61	98	64	34	1
EXLA62	150	64	34	1
EXLA64	185	64	34	1
EXLA80	75	80	57	1
EXLA81	125	80	57	1
EXLA82	175	80	57	1
EXLA83	250	80	52	1
EXLA102	100	100	80	1
EXLA103	160	100	80	1
EXLA101	200	100	80	1
EXLA100	230	100	110	1
EXLA122	122	120	80	1
EXLA120	122	120	90	1
EXLA124	220	120	80	1
EXLA121	220	120	90	1
EXLA128	220	120	120	1
EXLA126	360	120	80	1
EXLA140	140	140	90	1
EXLA141	200	140	90	1
EXLA160	160	160	90	1
EXLA161	260	160	90	1
EXLA162	360	160	90	1
EXLA163	560	160	90	1
EXLA181	180	180	100	1
EXLA180	280	180	100	1
EXLA234	200	230	110	1
EXLA235	200	230	180	1
EXLA230	280	230	110	1
EXLA231	330	230	110	1
EXLA236	330	230	180	1
EXLA232	400	230	110	1
EXLA238	400	230	224	1
EXLA233	600	230	110	1
EXLA310	400	310	110	1
EXLA315	400	310	140	1
EXLA311	400	310	180	1
EXLA316	400	310	226	1
EXLA312	600	310	110	1
EXLA313	600	310	180	1
EXLA600	600	600	200	1